# Madrid - Ceiling

AIC8844 21.50 in

JOB NAME: TYPE: NOTES:

# DESCRIPTION

Our shallow bowl collection offers simple classic lines in a low-profile alternative. When low to mid-height ceiling applications present themselves, this family complements contemporary and transitional styling. The family includes pendant, chandelier, wall-mounted, and ceiling models to illuminate and enhance the visual environment you're creating.

## FEATURES & BENEFITS

- Opal acrylic diffuser enhances a space with filtered illumination
- Spun metal trim ring adds high-quality, decorative element to fixture
- Optional finial available
- Handcrafted in USA

#### SPECIFICATIONS

- LIGHT SOURCE: White LED light engine
- CRI: 80+ or 90+
- LUMEN MAINTENANCE: L70 = >50,000 Hrs.
- CCT: 2700K, 3000K, 3500K, 4000K, 5000K
- DRIVER: Integral Class 2 power supply standard
- DIMMING: 0-10V controls standard to 10% on LED light engines
- **CONTROLS:** Contact factory for control options (e.g., Lutron Athena, Current NX, nLight, Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- EMERGENCY: Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- **DIFFUSER:** Opal acrylic is standard; matte acrylic and hand painted lenses optional
- **CONSTRUCTION:** Formed metal construction provides durable protection for internal components and is recyclable
- **MOUNTING:** Aluminum cover fits over a standard 4" octagonal junction box
- MODIFICATIONS: Consult factory for all modification requests




EMR



• **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

## DIMENSIONS



## **CONFIGURATOR**

To configure your spec sheet online, go to <u>www.spilighting.com/AIC8844</u>. Not all options are available in all configurations; consult factory for details.

#### **Required Field \***



## A - LIGHT SOURCE \*

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

L22W | White 22W LED Light Engine | Delivered Lumens: 1,107

L43W | White 43W LED Light Engine | Delivered Lumens: 2,214

See last page for finish options

## **B - VOLTAGE \***

120-277V | Universal Voltage



## **C - LAMP OPTIONS \***

Apply multiplier from chart for delivered lumens at other CCT's and CRI's.

<b>2700K  </b> 2700K CCT
<b>ЗОООК  </b> ЗОООК ССТ
<b>3500К  </b> 3500К ССТ
<b>4000K</b>   4000K CCT
<b>5000К  </b> 5000К ССТ

80 CRI	90 CRI
1.00	0.84
1.00	0.84
1.00	0.84
1.00	0.84
1.00	0.84
	1.00 1.00 1.00 1.00

## D - CRI \*

DF_80	l	(default)	
90			

## **E - DIFFUSER \***

# DF\_OA | Opal Acrylic Diffuser Lens (default)

- HP01 | Silver Hand Painted Acrylic Diffuser
- HP02 | Beige Hand Painted Acrylic Diffuser
- HP03 | Amber Hand Painted Acrylic Diffuser
- MA01 | Matte Acrylic Diffuser Lens



## **F - EMERGENCY**

10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.

**EMR** | Emergency Battery Remote

## **G - BOWL OPTIONS**

**FIN** | Finial (See last page for finish options)



# H - CANOPY

SP | Canopy Spacer

# I - OPTIONS

**F** | Fusing



## **Standard Finishes**

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing <u>contact@spilighting.com</u>. Please note, finishes may not be available in all configurations.

#### **Paint Colors**

PT01 RAL9003 Signal White (Gloss)	PT51 Matte White (Textured)	PT02 White (Textured)	PT04 RAL9001 Cream (Textured)	PT67 RAL7044 Silk Grey (Textured)	
PT53 RAL7035 Light Grey (Textured)	PT54 RAL7037 Dusty Grey (Textured)	PT55 RAL7012 Basalt Grey (Textured)	PT56 RAL7016 Anthracite Grey (Textured)	PT11 Black (Textured)	
PT57 RAL1015 Light Ivory (Textured)	PT58 RAL8004 Copper Brown (Textured)	PT59 RAL6021 Pale Green (Textured)	PT60 RAL1019 Grey Beige (Textured)	PT61 RAL7006 Beige Grey (Textured)	
PT62 RAL1003 Signal Yellow (Textured)	PT63 RAL3001 Signal Red (Textured)	PT64 RAL6001 Emerald Green (Textured)	PT65 RAL5005 Signal Blue (Textured)	PT66 RAL5003 Sapphire Blue (Textured)	

#### **Metallic Paint Colors**

			Bronze (Metallic Textured)	Dark Bronze (Metallic Gloss)	
PT46					
Aluminum (Metallic Textured)					

## **Brushed Aluminum**

BAL	
Brushed Aluminum	

#### **Brushed Brass**

BBR	
Brushed Solid Brass	

#### Polished-Tinted Brass

ATBR	DTBR	PBR	
Antique Tinted Brass	Dark Tinted Brass	Polished Brass	

#### **Plated Steel**



#### **Polished Plated Brass**

CPBR	10000	SNBR	
Chrome Plated Polished Brass		Satin Nickel Plated Brass	
			-



# **Specialty Finishes**



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.