

# Novato 2" Lines + Arcs

AIP12237 2.00 in | Connectors

JOB NAME:

TYPE:

NOTES:

## DESCRIPTION

This revolutionary modular system of luminous lines empowers you to create an infinite array of designs with ease, using all standard products. Get creative with crisp linear runs, precise angles, flowing curves, and sweeping elevation changes. There's no limit to what you can design with these architectural building blocks of light.


Impeccably designed with continuous illumination, Novato 2" Lines + Arcs exhibits clean lines with no breaks in the light. Luminous on three sides, it adds dimension by broadening the distribution of light. Plus, efficacy surpasses 100 lumens per watt! For a complimentary lighting layout, contact our applications team at [SPItteam@spilighting.com](mailto:SPItteam@spilighting.com).

## FEATURES & BENEFITS

- Slim 2"x2" line of light
- Three-sided luminous form brightens horizontal and vertical planes
- 70% direct/30% indirect distribution
- Up to 1,135 lm/ft
- Provides functional lighting with comfortable luminance levels
- Ideal for separating open offices, providing wayfinding, or adding markings
- Up to 550' of continuous light with just one power drop
- Maneuvers easily around obstructions
- Easy daisy chain wiring simplifies installation
- Hidden internal aircraft cable grippers are easy to adjust
- Luminous Lines (AIP12234), Arcs (AIP12235), and Elevation Changes (AIP12236) are ordered separately
- Handcrafted in USA

## SPECIFICATIONS


- **LIGHT SOURCE:** White LED light engine
- **CRI:** 80+ or 90+
- **LUMEN MAINTENANCE:** L80 = >36,000 Hrs.
- **EFFICACY:** 106 lm/W delivered
- **CCT:** 2700K, 3000K, 3500K, 4000K, 5000K
- **VOLTAGE:** 120-277V standard
- **DRIVER:** Integral Class 2 power supply. Power drop kit required



for each continuous run; see catalog CPS12238 to order.  
Connect power drops anywhere along the run.

- **MAX AMBIENT OPERATING TEMP:** 34.5°C (94°F)
- **DIMMING:** 1% minimum dim level standard
- **CONTROLS:** 0-10V standard. Lutron Athena and Current NX optional. Contact factory for other controls (e.g., nLight AIR, Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi).
- **INTEGRATED SURGE PROTECTION:** LED components are protected against minor surge events
- **DIFFUSER:** Matte opal acrylic
- **CONSTRUCTION:** Housing fabricated from 6000 series aluminum
- **FINISH:** Choose from 26 standard thermoset polyester powder coat paint colors or various metal finishes. RAL®, Pantone®, or custom finishes available upon request.
- **MODIFICATIONS:** Consult factory for all modification requests, including alternate configurations
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

DIMENSIONS



| + CONN | W              | L1             | L2               | OAH               |
|--------|----------------|----------------|------------------|-------------------|
|        | 2 in<br>5.1 cm | 24 in<br>61 cm | 12 in<br>30.5 cm | 48 in<br>121.9 cm |

Mounting Weight: Approximate: 5 lb (3 kg)

| L CONN | W              | L2               | OAH               |
|--------|----------------|------------------|-------------------|
|        | 2 in<br>5.1 cm | 12 in<br>30.5 cm | 48 in<br>121.9 cm |

Mounting Weight: Approximate: 5 lb (3 kg)

| T CONN | W              | L1             | L2               | OAH               |
|--------|----------------|----------------|------------------|-------------------|
|        | 2 in<br>5.1 cm | 24 in<br>61 cm | 12 in<br>30.5 cm | 48 in<br>121.9 cm |

Mounting Weight: Approximate: 5 lb (3 kg)

| 120° V CONN | W              | L2               | OAH               |
|-------------|----------------|------------------|-------------------|
|             | 2 in<br>5.1 cm | 12 in<br>30.5 cm | 48 in<br>121.9 cm |

Mounting Weight: Approximate: 5 lb (3 kg)

| 120° Y CONN | W              | L2               | OAH               |
|-------------|----------------|------------------|-------------------|
|             | 2 in<br>5.1 cm | 12 in<br>30.5 cm | 48 in<br>121.9 cm |

Mounting Weight: Approximate: 5 lb (3 kg)

CONFIGURATOR

To configure your spec sheet online, go to [www.spilighting.com/AIP12237](http://www.spilighting.com/AIP12237). Not all options are available in all configurations; consult factory for details.

Required Field \*

|                     |               |                 |          |               |      |           |           |                                |
|---------------------|---------------|-----------------|----------|---------------|------|-----------|-----------|--------------------------------|
| Catalog<br>AIP12237 | Light Source* | Primary Finish* | Voltage* | Lamp Options* | CRI* | Controls* | Mounting* | Other Than<br>Standard Options |
|                     | A             |                 | B        | C             | D    | E         | F         | G                              |

A - LIGHT SOURCE \*

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application. Alternative wattages available upon request.

T CONNECTOR

- ☐ **T CONN-L15W** | White 15W LED Light Engine | Delivered Lumens: 1,602
- ☐ **T CONN-L30W** | White 30W LED Light Engine | Delivered Lumens: 3,204

L CONNECTOR

- ☐ **L CONN-L10W** | White 10W LED Light Engine | Delivered Lumens: 1,068
- ☐ **L CONN-L20W** | White 20W LED Light Engine | Delivered Lumens: 2,136

+ CONNECTOR

- ☐ **+ CONN-L20W** | White 20W LED Light Engine | Delivered Lumens: 2,136
- ☐ **+ CONN-L40W** | White 40W LED Light Engine | Delivered Lumens: 4,272

120° Y CONNECTOR

- ☐ **120° Y CONN-L15W** | White 15W LED Light Engine | Delivered Lumens: 1,602
- ☐ **120° Y CONN-L30W** | White 30W LED Light Engine | Delivered Lumens: 3,204

120° V CONNECTOR

- ☐ **120° V CONN-L10W** | White 10W LED Light Engine | Delivered Lumens: 1,068
- ☐ **120° V CONN-L20W** | White 20W LED Light Engine | Delivered Lumens: 2,136

See last page for finish options

B - VOLTAGE \*

- ☐ **120-277V** | Universal Voltage

C - LAMP OPTIONS \*

Apply multiplier from chart for delivered lumens at other CCT's and CRI's.

- ☐ 2700K | 2700K CCT
- ☐ 3000K | 3000K CCT
- ☐ 3500K | 3500K CCT
- ☐ 4000K | 4000K CCT
- ☐ 5000K | 5000K CCT

|       | 80 CRI | 90 CRI |
|-------|--------|--------|
| 2700K | 0.91   | 0.77   |
| 3000K | 0.94   | 0.80   |
| 3500K | 0.97   | 0.82   |
| 4000K | 1.00   | 0.85   |
| 5000K | 1.00   | 0.85   |

D - CRI \*

- ☐ DF\_80 | (default)
- ☐ 90

E - CONTROLS \*

Extended lead times may apply for controls other than 0-10V. Contact factory for additional control options such as nLight AIR, Enlighted, Encelium, Wattstopper, WaveLinx, Casambi, or others.

- ☐ DF\_DIM1 | 0-10V Control, 1% Dimming (default)
- ☐ AWRN <sup>1</sup> | Lutron Athena Wireless Node, 1% Dimming
- ☐ NX <sup>1</sup> | Current NX Wireless, 1% Dimming

<sup>1</sup> Contact factory for complimentary layout including controls package.

F - MOUNTING \*

For mounting center information, go to <https://www.spilighting.com/AIP12237> > Downloads > Install Sheets. Power drop canopy mounts to standard 4" octagonal junction box. Field adjustable aircraft cables allow fixture to be mounted at an application appropriate height (up to OAH). The aircraft ceiling coupler can be connected to the power drop canopy or can be separated from the power drop canopy to gain flexibility in mounting. See Downloads on website for mounting center measurements. Aircraft cable suspension uses ceiling coupler to mount to structure above. Coupler accepts 1/4-20 threaded rod or can be anchored using through hole (hardware by others). INSTALLATION NOTES: During installation, the contractor is responsible for using the actual fixtures to ensure accurate mounting centers from one fixture to the next along the length of the linear run. All ends of Connectors are joiners. Sections do not come with a power drops; see CPS12238 to order separately. Contact the factory for help determining how many drops your layout requires.

- ☐ DF\_AC | Aircraft Cable (default)

G - OTHER THAN STANDARD OPTIONS

---

Specify overall height required from ceiling to the bottom of the fixture.

**OAH** | Pendant suspension length other than standard   Length:

## Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing [contact@spilighting.com](mailto:contact@spilighting.com). Please note, finishes may not be available in all configurations.

### Paint Colors

|   |  |   |   |   |
|---|--|---|---|---|
| <b>PT01</b><br>RAL9003 Signal White (Gloss)     | <b>PT51</b><br>Matte White (Textured)          | <b>PT02</b><br>White (Textured)                 | <b>PT04</b><br>RAL9001 Cream (Textured)           | <b>PT67</b><br>RAL7044 Silk Grey (Textured)     |
| <b>PT53</b><br>RAL7035 Light Grey (Textured)    | <b>PT54</b><br>RAL7037 Dusty Grey (Textured)   | <b>PT55</b><br>RAL7012 Basalt Grey (Textured)   | <b>PT56</b><br>RAL7016 Anthracite Grey (Textured) | <b>PT11</b><br>Black (Textured)                 |
| <b>PT57</b><br>RAL1015 Light Ivory (Textured)   | <b>PT58</b><br>RAL8004 Copper Brown (Textured) | <b>PT59</b><br>RAL6021 Pale Green (Textured)    | <b>PT60</b><br>RAL1019 Grey Beige (Textured)      | <b>PT61</b><br>RAL7006 Beige Grey (Textured)    |
| <b>PT62</b><br>RAL1003 Signal Yellow (Textured) | <b>PT63</b><br>RAL3001 Signal Red (Textured)   | <b>PT64</b><br>RAL6001 Emerald Green (Textured) | <b>PT65</b><br>RAL5005 Signal Blue (Textured)     | <b>PT66</b><br>RAL5003 Sapphire Blue (Textured) |

### Metallic Paint Colors

|   |  |  |   |   |
|---|--|--|---|---|
| <b>PT22</b><br>Platinum (Metallic Gloss)    | <b>PT48</b><br>Brass (Metallic Textured) | <b>PT28</b><br>Dark Stainless (Metallic Gloss) | <b>PT49</b><br>Bronze (Metallic Textured) | <b>PT32</b><br>Dark Bronze (Metallic Gloss) |
| <b>PT46</b><br>Aluminum (Metallic Textured) |  |  |   |   |

## Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.