Harbor - Triple Bars

AIW8277 14.50 in

SPILIGHTING PROJECT DETAILS

JOB NAME:

TYPE:

NOTES:

DESCRIPTION

The Harbor series sconce is available with a wide variety of adornment. Highlighting the fixture are three 1/2" vertical solid brass bars.

FEATURES & BENEFITS

- Solid metal accents add high-quality, decorative element to fixture
- Compliant with Americans with Disabilities Act (ADA) requirements
- Optional VAN (vanity mount) features solid end caps for a fully enclosed fixture
- Exterior family fixtures available to carry a consistent lighting design throughout a project
- · Handcrafted in USA

SPECIFICATIONS

- LIGHT SOURCE: White LED light engine
- CRI: 80+ or 90+
- LUMEN MAINTENANCE: L70 = >50.000 Hrs.
- CCT: 2700K, 3000K, 3500K, 4000K, 5000K
- DRIVER: Integral Class 2 power supply standard
- DIMMING: 1% minimum dim level standard
- CONTROLS: 0-10V standard. Lutron Athena and nLight AIR optional. Contact factory for other controls (e.g., Enlighted, Encelium, Wattstopper, WaveLinx, Current NX, or Casambi)
- EMERGENCY: Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- DIFFUSER: Formed opal acrylic lens; matte acrylic optional.
 Prismatic top lens and bottom lens standard with any LED module. They shield direct view of the lamp in applications where views above or below the fixture are possible and prevent external objects from entering the fixture.
- MOUNTING: Mounts to standard 4" octagonal junction box












- MODIFICATIONS: Consult factory for all modification requests
- APPROVALS: ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

DIMENSIONS



W	H	D	MC	
7 in	14.5 in	4 in	7.2 in	
17.8 cm	36.8 cm	10.2 cm	18.3 cm	
17.8 cm	36.8 CM	10.2 cm	18.3 cm	

Mounting Weight
Approximate: 25 lb (12 kg)

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/AIW8277. Not all options are available in all configurations; consult factory for details.

Required Field *

Catalog	Light Source*	Primary Finish*	Voltage*	Lamp Options*	CRI*	Controls*	Diffuser*	Mounting	Emergency
AIW8277									
								Finish:	
		٨	D	0	D			C	ш

A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

L29W | White 29W LED Light Engine | Delivered Lumens: 1,966

L14W | White 14W LED Light Engine | Delivered Lumens: 983

See last page for finish options

B-VOLTAGE*

☐ 120-277V | Universal Voltage

C-LAMP OPTIONS*

Apply multiplier from chart for delivered lumens at other CCT's and CRI's. **2700K | 2700K CCT** ■ 3000K | 3000K CCT 3500K | 3500K CCT ☐ 4000K | 4000K CCT **■ 5000K |** 5000K CCT 90 CRI 1.00 0.84 1.00 0.84 1.00 0.84 1.00 0.84 D - CRI * **DF_80** | (default) 90 **E - CONTROLS *** Extended lead times may apply for controls other than 0-10V. Contact factory for additional control options such as Enlighted, Encelium, Wattstopper, WaveLinx, Casambi, Current NX, or others. **DF_DIM1** | 0-10V Control, 1% Dimming (default) AWNR | Lutron Athena Wireless Node, 1% Dimming NLTA | Acuity nLight Air, 1% Dimming F - DIFFUSER * ☐ **DF_OA** | Opal Acrylic Diffuser Lens (default) MA01 | Matte Acrylic Diffuser Lens

G-MOUNTING

OA

Vanity mount features solid end caps.

VAN | Vanity Mount (See last page for finish options)

MA01



H - EMERGENCY

10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.					
☐ EMR Emergency Battery Remote					



Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

PT01 RAL9003 Signal White (Gloss)	PT51 Matte White (Textured)	PT02 White (Textured)	PT04 RAL9001 Cream (Textured)	PT67 RAL7044 Silk Grey (Textured)
PT53 RAL7035 Light Grey (Textured)	PT54 RAL7037 Dusty Grey (Textured)	PT55 RAL7012 Basalt Grey (Textured)	PT56 RAL7016 Anthracite Grey (Textured)	PT11 Black (Textured)
PT57 RAL1015 Light Ivory (Textured)	PT58 RAL8004 Copper Brown (Textured)	PT59 RAL6021 Pale Green (Textured)	PT60 RAL1019 Grey Beige (Textured)	PT61 RAL7006 Beige Grey (Textured)
PT62 RAL1003 Signal Yellow (Textured)	PT63 RAL3001 Signal Red (Textured)	PT64 RAL6001 Emerald Green (Textured)	PT65 RAL5005 Signal Blue (Textured)	PT66 RAL5003 Sapphire Blue (Textured)

Brushed Copper



Metallic Paint Colors

PT22	PT48	PT28	PT49	PT32	
Platinum (Metallic Gloss)	Brass (Metallic Textured)	Dark Stainless (Metallic Gloss)	Bronze (Metallic Textured)	Dark Bronze (Metallic Gloss)	
PT46					
Aluminum (Metallic Textured)					

Polished Copper



Brushed Aluminum



Brushed Brass



Polished-Tinted Brass

ATBR	DTBR	PBR	
Antique Tinted Brass	Dark Tinted Brass	Polished Brass	

Polished Plated Brass

CPBR	1000	SNBR	
Chrome Plated Polished Brass		Satin Nickel Plated Brass	
	_		



Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.

