

# IMPORTANT SAFETY AND INSTALLATION INSTRUCTIONS

**WARNING:** Risk of fire and electrical shock. This product is to be installed by a qualified electrician only.

**CAUTION:** When using electrical equipment, basic safety precautions should always be followed including the following: Read all instructions carefully before installation and save

for future use. Make sure installation and all connections are in accordance with National Electrical Code and any local regulations. To avoid possible electrical shock, be sure that power supply is turned off before installing or servicing this fixture. Servicing should be performed by qualified service personnel.

These instructions do not claim to cover all details or variations. When additional information is desired, please contact your SPI representative.

## BEAM ICS - 1.4" CANOPY MOUNT (LED)

### MOUNTING DETAIL - OLD WORK

**OLD-WORK CLIP SCREW**  
TIGHTEN SCREW TO EXPAND OLD-WORK CLIPS

**OLD-WORK CLIP**  
EXPAND TO SECURE MOUNTING HUB TO WALL

**MOUNTING HUB**  
INSTALL HUB IN 1.125" DIA. HOLE. HUB TO BE MOUNTED WITH CLIPS ORIENTATED AS SHOWN ON TOP AND BOTTOM OF HUB. EXPAND OLD-WORK CLIPS TO SECURE TO WALL.

**CANOPY COVER**  
THREAD COVER ONTO MOUNTING HUB

**MC = 53.0"**

**LEAD WIRES**  
TO REMOTE POWER SUPPLY

**3/8" FLEXIBLE CONDUIT**  
5 FT LONG

**CANOPY COVER**  
THREAD COVER ONTO MOUNTING HUB

**MOUNTING HUB**  
INSTALL HUB IN 1.125" DIA. HOLE. HUB TO BE MOUNTED WITH CLIPS ORIENTATED AS SHOWN ON TOP AND BOTTOM OF HUB. EXPAND OLD-WORK CLIPS TO SECURE TO WALL.

FIXTURE MOUNTED TO 1.125" DIA. HOLES IN WALL  
FIXTURE IS REVERSIBLE. THE SUPPLY LEADS MAY BE LOCATED AT EITHER END.

### NEW CONSTRUCTION - MOUNTING PLATE

FOR NEW CONSTRUCTION. PLATE TO BE MOUNTED DIRECTLY TO BLOCKING. 1.125" DIA. (OR LARGER) HOLE REQUIRED IN BLOCKING.

**OLD-WORK CLIP SCREW**  
REMOVE SCREW FROM OLD-WORK CLIP. SCREW TO BE USED TO SECURE MOUNTING HUB TO OPTIONAL MOUNTING PLATE.

### MOUNTING DETAIL - NEW CONSTRUCTION

3/23/22  
IS61498X