Madrid (4) Bowl Chandelier

AIP8687 21.50 in

JOB NAME:

TYPE:

NOTES:



DESCRIPTION

Our shallow bowl collection offers simple classic lines in a low-profile alternative. When low to mid-height ceiling applications present themselves, this family complements contemporary and transitional styling. The family includes pendant, chandelier, wall-mounted, and ceiling models to illuminate and enhance the visual environment you're creating.

FEATURES & BENEFITS

- Opal acrylic diffuser enhances a space with filtered illumination
- Spun metal trim ring adds high-quality, decorative element to fixture
- · Handcrafted in USA

SPECIFICATIONS

- LIGHT SOURCE: White LED light engine
- CRI: 80+ or 90+
- LUMEN MAINTENANCE: L70 = >50,000 Hrs.
- CCT: 2700K, 3000K, 3500K, 4000K, 5000K
- DRIVER: Integral Class 2 power supply standard
- DIMMING: 0-10V controls standard to 10% on LED light engines
- CONTROLS: Contact factory for control options (e.g., Lutron Athena, Current NX, nLight, Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- EMERGENCY: Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- DIFFUSER: Opal acrylic is standard; matte acrylic and hand painted lenses optional. Any upward facing LEDs will be covered with a protective lens.
- **CONSTRUCTION:** Formed metal construction provides durable protection for internal components and is recyclable
- MODIFICATIONS: Consult factory for all modification requests
- APPROVALS: ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications










DIMENSIONS



W	H	OAH	L
21.5 in	7.7 in	33 in	65.2 in
54.6 cm	19.6 cm	83.8 cm	165.6 cm
Mounting \ Approxima	Veight te: 150 lb (69	kg)	

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/AIP8687. Not all options are available in all configurations; consult factory for details.

Required Field *



A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

(4) L50W (4 HEAD) White 50W	LED Li	ght Engine Delivered Lumens: 19,869
(4) L100W (4 HEAD) White 100	W LED	Light Engine Delivered Lumens: 39,740
Cust_Out		
Lumen Calculator: Enter Lum	nens o	r Watts if different than displayed
	LU	Min 19800 - Max 39600
	W	Min 200.0 - Max 400.0

See last page for finish options

*For requests outside Min-Max range, please contact factory.

B-VOLTAGE*

C - LAMP OPTIONS *

Apply multiplier from chart for delivered lumens at other CCT's and CRI's.

2700K	2700K CC1

3000К | 3000К ССТ

3500К | 3500К ССТ

☐ 4000K | 4000K CCT

	80 CRI	90 CRI
2700K	1.00	0.84
3000K	1.00	0.84
3500K	1.00	0.84
4000K	1.00	0.84
5000K	1.00	0.84

D - CRI *

DF_80 | (default)

_ 90

E - DIFFUSER *

☐ DF_OA | Opal Acrylic Diffuser Lens (default)

☐ HP01 | Silver Hand Painted Acrylic Diffuser

HP02 | Beige Hand Painted Acrylic Diffuser

HP03 | Amber Hand Painted Acrylic Diffuser

MA01 | Matte Acrylic Diffuser Lens











F - MOUNTING *

Mounts to standard 4" octagonal junction box with auxiliary mounting holes. Additional support required (by others). Canopy is 6.5" diameter with a 45 degree swivel.

DF_STM | Stem Mount (default)

G - EMERGENCY

10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.

H-OPTIONS

 $\begin{tabular}{ll} \hline & KA01 & Angled Aircraft Cable Kit (to Transition Plate/Canopy) \\ \hline \end{tabular}$ (See last page for finish options)

KR01 | Angled Stem Multi Kit (to Transition Plate) (See last page for finish options)

KS01 | Straight Stem Multi Kit (to Transition Plate) (See last page for finish options)

F | Fusing







I - OTHER THAN STANDARD OPTIONS

Specify overall height required from ceiling to the bottom of the fixture.

OAH | Pendant suspension length other than standard | Length:



Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

PT01	PT51	PT02	PT04 RAL9001 Cream (Textured)	PT67
RAL9003 Signal White (Gloss)	Matte White (Textured)	White (Textured)		RAL7044 Silk Grey (Textured)
PT53 RAL7035 Light Grey (Textured)	PT54 RAL7037 Dusty Grey (Textured)	PT55 RAL7012 Basalt Grey (Textured)	PT56 RAL7016 Anthracite Grey (Textured)	PT11 Black (Textured)
PT57	PT58 RAL8004 Copper Brown (Textured)	PT59	PT60	PT61
RAL1015 Light Ivory (Textured)		RAL6021 Pale Green (Textured)	RAL1019 Grey Beige (Textured)	RAL7006 Beige Grey (Textured)
PT62 RAL1003 Signal Yellow (Textured)	PT63 RAL3001 Signal Red (Textured)	PT64 RAL6001 Emerald Green (Textured)	PT65 RAL5005 Signal Blue (Textured)	PT66 RAL5003 Sapphire Blue (Textured)

Metallic Paint Colors

PT22	PT48	PT28	PT49	PT32	
Platinum (Metallic Gloss)	Brass (Metallic Textured)	Dark Stainless (Metallic Gloss)	Bronze (Metallic Textured)	Dark Bronze (Metallic Gloss)	
PT46					
Aluminum (Motallia Taxturad)					

Brushed Aluminum

BAL	
Brushed Aluminum	

Brushed Brass



Polished-Tinted Brass

ATBR	DTBR	PBR
Antique Tinted Brass	Dark Tinted Brass	Polished Brass

Plated Steel

ANST	BBST	CPST	1000	PBST	SNST	
Antique Brass Plated Steel	Brushed Brass Plated Steel	Chrome Plated Steel		Polished Brass Plated Steel	Satin Nickel Steel	
			_			

Polished Plated Brass

CPBR	1000	SNBR	
Chrome Plated Polished Brass		Satin Nickel Plated Brass	
	_		THE REAL PROPERTY.



Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.

