

Vallejo LC - Ceiling

SIC12100 8.00 in

SPILIGHTING

PROJECT DETAILS

JOB NAME:

TYPE:

NOTES:

DESCRIPTION

Add elegance and radiance to your most discerning spaces. This luminous cylinder's integral regressed downlight delivers correct light levels where needed. Ambient illumination provides a gentle visual warm-up to the higher output downlight source while adding light to the vertical plane to open up spaces. Meticulous attention to detail ensures suitability for the highest-end applications. Integral power supply simplifies installation.

FEATURES & BENEFITS

- Fixture has a bi-planar ambient finished bottom detail with or without the regressed downlight component
- Integral regressed downlight available in 1900lm and beam spread of narrow, medium, wide, or very wide
- Matte acrylic ambient cylinder diffuser is balanced with the proper amount of illumination while providing a sensible wattage allotment
- Integrated LED luminaire design features a sophisticated passive cooling system with integrated heat sink
- Ambient and downlight components are standard with separate switching and 0-10v dimming
- Handcrafted in USA




EMR

SPECIFICATIONS

- **LIGHT SOURCE:** White LED light engine (contact factory for RGBW or Tunable White)
- **CRI:** 80+ or 90+
- **LUMEN MAINTENANCE:** L70 = >50,000 Hrs.
- **EFFICACY:** up to 103 lm/W delivered
- **CCT:** 2700K, 3000K, 3500K, 4000K, 5000K
- **VOLTAGE:** 120-277V standard
- **DRIVER:** Integral Class 2 power supply standard
- **DIMMING:** 0-10V controls standard to 1% on LED light engines
- **EMERGENCY:** Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.

- **INTEGRATED SURGE PROTECTION:** LED components are protected against minor surge events
- **DIFFUSER:** White matte acrylic diffuser standard; white gloss acrylic diffuser optional
- **CONSTRUCTION:** Aluminum
- **FINISH:** End plate and mounting components finished to match. To specify separately, contact factory. Choose from 26 standard thermoset polyester powder coat paint colors. RAL®, Pantone®, or custom finishes available upon request.
- **MOUNTING:** Mounts to standard 4" octagonal junction box
- **MODIFICATIONS:** Consult factory for all modification requests, including RGBW or Tunable White
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

DIMENSIONS



| W | H1 | H2 |
|---------------------------|---------|---------|
| 8 in | 11.1 in | 13.3 in |
| 20.3 cm | 28.2 cm | 33.8 cm |
| Mounting Weight | | |
| Approximate: 15 lb (7 kg) | | |

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/SIC12100. Not all options are available in all configurations; consult factory for details.

Required Field *

| | | | | | | | | |
|----------|---------------|-----------------|----------|---------------|------|----------------------|-----------|-----------|
| Catalog | Light Source* | Primary Finish* | Voltage* | Lamp Options* | CRI* | Light Source Option* | Diffuser* | Emergency |
| SIC12100 | | | | | | | | |
| | A | | B | C | D | E | F | G |

A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application. Alternative wattages available upon request.

☐ **L10W** | White 10W LED Light Engine | Delivered Lumens: 980

See last page for finish options

B - VOLTAGE *

☐ 120-277V | Universal Voltage

C - LAMP OPTIONS *

Apply multiplier from charts for delivered lumens at other CCT's and CRI's.

- ☐ 2700K | 2700K CCT
- ☐ 3000K | 3000K CCT
- ☐ 3500K | 3500K CCT
- ☐ 4000K | 4000K CCT
- ☐ 5000K | 5000K CCT

| MAIN BODY LIGHT | | | DOWN LIGHT | | |
|-----------------|--------|--------|------------|--------|--------|
| | 80 CRI | 90 CRI | | 80 CRI | 90 CRI |
| 2700K | 1.00 | 0.84 | 2700K | 0.92 | 0.78 |
| 3000K | 1.00 | 0.84 | 3000K | 0.95 | 0.82 |
| 3500K | 1.00 | 0.84 | 3500K | 0.97 | 0.86 |
| 4000K | 1.00 | 0.84 | 4000K | 1.00 | 0.88 |
| 5000K | 1.00 | 0.84 | 5000K | 1.00 | 0.88 |


D - CRI *

- ☐ DF_80 | (default)
- ☐ 90

E - LIGHT SOURCE OPTION *


If you're specifying a downlight option, layer the ambient and downlight IES files. Downlight CCT will match the Lamp Options selection above. Please choose one:

- ☐ 18W-26° Narrow | 18W (1900 delivered lumens) Downlight - 26° Beam
- ☐ 18W-40° Medium | 18W (1900 delivered lumens) Downlight - 40° Beam
- ☐ 18W-55° Wide | 18W (1900 delivered lumens) Downlight - 55° Beam
- ☐ 18W-90° Very Wide | 18W (1900 delivered lumens) Downlight - 90° Beam
- ☐ No DL | No Downlight



F - DIFFUSER *

- ☐ **DF_MA01** | Matte Acrylic Diffuser Lens (default)
- ☐ **OA** | White Gloss Acrylic Diffuser



G - EMERGENCY

10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.

- ☐ **EMR** | Emergency Battery Remote

Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

| | | | | |
|---|--|---|---|---|
| PT01 RAL9003 Signal White (Gloss) | PT51 Matte White (Textured) | PT02 White (Textured) | PT04 RAL9001 Cream (Textured) | PT67 RAL7044 Silk Grey (Textured) |
| PT53 RAL7035 Light Grey (Textured) | PT54 RAL7037 Dusty Grey (Textured) | PT55 RAL7012 Basalt Grey (Textured) | PT56 RAL7016 Anthracite Grey (Textured) | PT11 Black (Textured) |
| PT57 RAL1015 Light Ivory (Textured) | PT58 RAL8004 Copper Brown (Textured) | PT59 RAL6021 Pale Green (Textured) | PT60 RAL1019 Grey Beige (Textured) | PT61 RAL7006 Beige Grey (Textured) |
| PT62 RAL1003 Signal Yellow (Textured) | PT63 RAL3001 Signal Red (Textured) | PT64 RAL6001 Emerald Green (Textured) | PT65 RAL5005 Signal Blue (Textured) | PT66 RAL5003 Sapphire Blue (Textured) |

Metallic Paint Colors

| | | | | |
|---|--|--|---|---|
| PT22 Platinum (Metallic Gloss) | PT48 Brass (Metallic Textured) | PT28 Dark Stainless (Metallic Gloss) | PT49 Bronze (Metallic Textured) | PT32 Dark Bronze (Metallic Gloss) |
| PT46 Aluminum (Metallic Textured) | | | | |

Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.