# London - Pendant

AIP8411 23.50 in

SPI LIGHTING
PROJECT DETAILS

JOB NAME:
TYPE:
NOTES:

## DESCRIPTION

London is part of our classic bowl collection, hallmarked by the proven simplicity and purity of timeless geometry. It features a deeper shape ideal for mid to high height ceiling applications. The family includes pendant, chandelier, wall-mounted, and ceiling models to illuminate and enhance the visual environment.



EMR


### FEATURES & BENEFITS

- Opal acrylic diffuser lens enhances a space with filtered illumination
- Spun metal trim ring adds high-quality, decorative element to fixture
- Handcrafted in USA

### SPECIFICATIONS

- **LIGHT SOURCE:** White LED light engine or incandescent
- **CRI:** 80+ or 90+
- **Lumen Maintenance:** L70 = >50,000 Hrs.
- **CCT**: Available LED color temperatures: 2700K, 3000K, 3500K, 4000K, 5000K
- **DRIVER:** LED versions feature integral Class 2 power supply standard
- **DIMMING:** 0-10V controls standard to 1% on LED light engines
- **CONTROLS:** Contact factory for control options (e.g., Lutron Athena, Current NX, nLight, Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- **EMERGENCY:** Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- **DIFFUSER:** Opal acrylic is standard; matte acrylic and hand painted lenses optional. Any upward facing LEDs will be covered with a protective lens.
- **MODIFICATIONS:** Consult factory for all modification requests
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

## DIMENSIONS




| W | H | OAH |
|---|---|---|
| 23.5 in<br>59.7 cm | 9.2 in<br>23.4 cm | 35 in<br>88.9 cm |

**Mounting Weight**
Approximate: 50 lb (23 kg)

## CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/AIP8411. Not all options are available in all configurations; consult factory for details.

**Required Field ***

| Catalog | Light Source* | Primary Finish* | Voltage* | Lamp Options* | CRI* | Diffuser* | Mounting* | Emergency | Bowl Options | Options | Other Than Standard Options |
|---|---|---|---|---|---|---|---|---|---|---|---|
| AIP8411 | | | | | | | | | | | |
| | | | | | | | | | Finish: | Finish: | |
| | A | | B | C | D | E | F | G | H | I | J |

## A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

- ☐ **L50W** | White 50W LED Light Engine | Delivered Lumens: 4,968
- ☐ **L100W** | White 100W LED Light Engine | Delivered Lumens: 9,935
- ☐ **1N300** [1] | 1INC300W/PS30

See last page for finish options

[1] Incandescent Lamp(s) Not Included

## B - VOLTAGE *

- ☐ **120-277V** | Universal Voltage
- ☐ **120V** [2] | 120 Volt

[2] For incandescent light source only

## C - LAMP OPTIONS *

Apply multiplier from chart for delivered lumens at other CCT's and CRI's. Not required with incandescent.

- ☐ **2700K** | 2700K CCT
- ☐ **3000K** | 3000K CCT
- ☐ **3500K** | 3500K CCT
- ☐ **4000K** | 4000K CCT
- ☐ **5000K** | 5000K CCT

| | 80 CRI | 90 CRI |
|---|---|---|
| 2700K | 1.00 | 0.84 |
| 3000K | 1.00 | 0.84 |
| 3500K | 1.00 | 0.84 |
| 4000K | 1.00 | 0.84 |
| 5000K | 1.00 | 0.84 |

## D - CRI *

- ☐ **DF_80** | (default)
- ☐ **90**

## E - DIFFUSER *

- ☐ **DF_OA** | Opal Acrylic Diffuser Lens (default)
- ☐ **HP01** | Silver Hand Painted Acrylic Diffuser
- ☐ **HP02** | Beige Hand Painted Acrylic Diffuser
- ☐ **HP03** | Amber Hand Painted Acrylic Diffuser
- ☐ **MA01** | Matte Acrylic Diffuser Lens




## F - MOUNTING *

Mounts to standard 4" octagonal junction box with auxiliary mounting holes. Canopy is 6.5" diameter with a 45 degree swivel.

- ☐ **DF_STM** | Stem Mount (default)

## G - EMERGENCY

10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.


- ☐ **EMR** | Emergency Battery Remote

## H - BOWL OPTIONS

☐ **FIN |** Finial (See last page for finish options)

## I - OPTIONS

☐ **KC01 |** Chain Kit (to Transition Plate) (See last page for finish options)
☐ **KR01 |** Angled Stem Multi Kit (to Transition Plate) (See last page for finish options)
☐ **KS01 |** Straight Stem Multi Kit (to Transition Plate) (See last page for finish options)
☐ **F |** Fusing


KC01


KR01


KS01

## J - OTHER THAN STANDARD OPTIONS

Specify overall height required from ceiling to the bottom of the fixture.

**OAH |** Pendant suspension length other than standard Length:

## Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

### Paint Colors

| | | | | |
|---|---|---|---|---|
| **PT01** RAL9003 Signal White (Gloss) | **PT51** Matte White (Textured) | **PT02** White (Textured) | **PT04** RAL9001 Cream (Textured) | **PT67** RAL7044 Silk Grey (Textured) |
| **PT53** RAL7035 Light Grey (Textured) | **PT54** RAL7037 Dusty Grey (Textured) | **PT55** RAL7012 Basalt Grey (Textured) | **PT56** RAL7016 Anthracite Grey (Textured) | **PT11** Black (Textured) |
| **PT57** RAL1015 Light Ivory (Textured) | **PT58** RAL8004 Copper Brown (Textured) | **PT59** RAL6021 Pale Green (Textured) | **PT60** RAL1019 Grey Beige (Textured) | **PT61** RAL7006 Beige Grey (Textured) |
| **PT62** RAL1003 Signal Yellow (Textured) | **PT63** RAL3001 Signal Red (Textured) | **PT64** RAL6001 Emerald Green (Textured) | **PT65** RAL5005 Signal Blue (Textured) | **PT66** RAL5003 Sapphire Blue (Textured) |

### Metallic Paint Colors

| | | | | |
|---|---|---|---|---|
| **PT22** Platinum (Metallic Gloss) | **PT48** Brass (Metallic Textured) | **PT28** Dark Stainless (Metallic Gloss) | **PT49** Bronze (Metallic Textured) | **PT32** Dark Bronze (Metallic Gloss) |
| **PT46** Aluminum (Metallic Textured) | | | | |

### Brushed Aluminum

| |
|---|
| **BAL** Brushed Aluminum |

### Brushed Brass

| |
|---|
| **BBR** Brushed Solid Brass |

### Polished-Tinted Brass

| | | |
|---|---|---|
| **ATBR** Antique Tinted Brass | **DTBR** Dark Tinted Brass | **PBR** Polished Brass |

### Plated Steel

| | | | | |
|---|---|---|---|---|
| **ANST** Antique Brass Plated Steel | **BBST** Brushed Brass Plated Steel | **CPST** Chrome Plated Steel | **PBST** Polished Brass Plated Steel | **SNST** Satin Nickel Steel |

### Polished Plated Brass

| | |
|---|---|
| **CPBR** Chrome Plated Polished Brass | **SNBR** Satin Nickel Plated Brass |

## Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.