INACTIVE SPEC SHEET

Marbles - Square

AIW8367 12.00 in



JOB NAME: TYPE:

NOTES:

DESCRIPTION

The Marbles series of wall sconces is perfect for unique, themed, or playful spaces. To create the look, eight marble colors are arranged randomly between 1/8" aluminum plates, producing a one-of-a-kind design for every fixture. An internal tempered, prismatic glass lens diffuses any view through the marbles. Meets ADA requirements. Choose from a palette of painted and metal finishes.

FEATURES & BENEFITS

- Iridescent glass marbles, in multiple colors, provide the ability to create a design in a unique and expressive fixture
- Choose a random marble configuration or contact factory to design a custom pattern
- Compliant with Americans with Disabilities Act (ADA) requirements
- Handcrafted in USA

SPECIFICATIONS

- LIGHT SOURCE: White LED light engine or incandescent
- LUMEN MAINTENANCE (LED): L70 = >50,000 Hrs.
- CCT: Available LED color temperatures: 3000K, 3500K, or 4000K
- DRIVER: LED versions feature integral Class II power supply standard
- **DIMMING:** 0-10V controls standard on LED light engines
- **EMERGENCY**: Emergency battery remote optional
- LENS: An internal tempered, prismatic glass lens diffuses any view through the marbles
- **CONSTRUCTION:** Formed metal construction provides durable protection for internal components and is recyclable
- MOUNTING: Mounts to standard 4" octagonal junction box
- MODIFICATIONS: Consult factory for all modification requests
- APPROVALS: ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications










DIMENSIONS



W	H	D	МС		
12 in 30.5 cm	12 in 30.5 cm		6 in		
Mounting \		. 0.2 0	. 0.2 0		
Approximate: 25 lb (12 kg)					

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/AIW8367. Not all options are available in all configurations; consult factory for details.

Required Field *



A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

L7W | White 7W LED Light Engine

L14W | White 14W LED Light Engine

2N60 1 | 2INC60W/T10/MED

See last page for finish options

¹ Incandescent Lamp(s) Not Included

B-VOLTAGE*

☐ 120-277V | Universal Voltage

120V 2 | 120 Volt

² For incandescent light source only

C - LAMP OPTIONS *
Delivered lumens shown are at 4000K CCT; apply multiplier for delivered lumens at other CCT.
□ 3000K ³ 3000K CCT
☐ 3500K ⁴ 3500K CCT
☐ 4000K 4000K CCT
³ Apply .95 multiplier for delivered lumens
⁴ Apply .97 multiplier for delivered lumens
D - LENS
Top lens and bottom lens standard with any LED module. Choose option only if specifying incandescent.
□ BL Bottom Lens
☐ TL Top Lens

Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

PT01	PT51	PT02	PT04	PT11
RAL9003 Signal White (Gloss)	Matte White (Textured)	White (Textured)	RAL9001 Cream (Textured)	Black (Textured)

Metallic Paint Colors

PT22 Platinum (Metallic Gloss)	PT48 Brass (Metallic Textured)	PT28 Dark Stainless (Metallic Gloss)	PT49 Bronze (Metallic Textured)	PT32 Dark Bronze (Metallic Gloss)	
Platifium (Metallic Gloss)	brass (wetanic rextured)	Dark Stailliess (Metallic Gloss)	bronze (Metallic Textured)	Dark Broffze (Metallic Gloss)	
PT46					
Aluminum (Metallic Textured)					

Brushed Aluminum

BAL	
Brushed Aluminum	

Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.