Stockholm - Ceiling

AIC8778 21.50 in

JOB NAME:

TYPE:

NOTES:



DESCRIPTION

Stockholm is part of our classic bowl collection, hallmarked by the proven simplicity and purity of timeless geometry. It features a deeper shape ideal for mid to high height ceiling applications. The family includes pendant, chandelier, wall-mounted, and ceiling models to illuminate and enhance the visual environment.

FEATURES & BENEFITS

- Opal acrylic diffuser lens enhances a space with filtered illumination
- Spun metal trim ring adds high-quality, decorative element to fixture
- · Handcrafted in USA

SPECIFICATIONS


- LIGHT SOURCE: White LED light engine or incandescent
- CRI: 80+ or 90+
- Lumen Maintenance: L70 = >50,000 Hrs.
- CCT: Available LED color temperatures: 2700K, 3000K, 3500K, 4000K, 5000K
- DRIVER: LED versions feature integral Class 2 power supply standard
- **DIMMING:** 0-10V controls standard to 10% on LED light engines
- CONTROLS: Contact factory for control options (e.g., Lutron Athena, Current NX, nLight, Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- EMERGENCY: Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- DIFFUSER: Opal acrylic is standard; matte acrylic and hand painted lenses optional
- **CONSTRUCTION:** Formed metal construction provides durable protection for internal components and is recyclable
- **MOUNTING:** Aluminum cover fits over a standard 4" octagonal junction box






- MODIFICATIONS: Consult factory for all modification requests
- APPROVALS: ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

DIMENSIONS





| W | H1 | H2 |
|---------|---------|---------|
| 21.5 in | 9.2 in | 11.2 in |
| 54.6 cm | 23.4 cm | 28.4 cm |

Mounting Weight
Approximate: 25 lb (12 kg)

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/AIC8778. Not all options are available in all configurations; consult factory for details.

Required Field *

| Catalog AIC8778 | Light course | Primary Finish* | Voltage* | Lamp Options* | CRI* | Diffuser* | Emergency | Bowl Options | Canopy | Options |
|--------------------|--------------|--------------------|----------|---------------|------|-----------|-----------|--------------|--------|---------|
| | | | | | | | | Finish: | | |
| | | ٨ | B | C | D | | Е | C | Н | 1 |

A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

| □ L29W I | White 20W | I FD Liaht | Engine | Delivered | l iimens. | 1 476 |
|----------|-----------|------------|--------|-----------|-----------|-------|
| | | | | | | |

See last page for finish options

L57W | White 57W LED Light Engine | Delivered Lumens: 2,952

³N60 1 | 3INC60W/A19

¹ Incandescent Lamp(s) Not Included

| | | 10 | | |
|---|-----|----|------------|--|
| u | _ \ | | A II - | |
| | | | | |

| | 120-277V | Universal Voltage |
|--|----------|-------------------|
|--|----------|-------------------|

C-LAMP OPTIONS*

Apply multiplier from chart for delivered lumens at other CCT's and CRI's. Not required with incandescent.

- **2700K |** 2700K CCT
- 3000K | 3000K CCT
- **3500K** | 3500K CCT
- ☐ 4000K | 4000K CCT
- **5000K |** 5000K CCT

| | 80 CRI | 90 CRI |
|-------|--------|--------|
| 2700K | 1.00 | 0.84 |
| 3000K | 1.00 | 0.84 |
| 3500K | 1.00 | 0.84 |
| 4000K | 1.00 | 0.84 |
| 5000K | 1.00 | 0.84 |

D - CRI *

DF_80 | (default)

90

E - DIFFUSER *

☐ **DF_OA** | Opal Acrylic Diffuser Lens (default)

☐ **HP01** | Silver Hand Painted Acrylic Diffuser

HP02 | Beige Hand Painted Acrylic Diffuser

☐ **HP03** | Amber Hand Painted Acrylic Diffuser

MA01 | Matte Acrylic Diffuser Lens



[☐] **120V ²** | 120 Volt

² For incandescent light source only

| 10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up. |
|--|
| ☐ EMR Emergency Battery Remote |
| G - BOWL OPTIONS |
| FIN Finial (See last page for finish options) |
| H - CANOPY |
| SP Canopy Spacer |
| - OPTIONS |
| □ F Fusing |



F - EMERGENCY

Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

| PT01 | PT51 | PT02 | PT04 RAL9001 Cream (Textured) | PT67 |
|---|--------------------------------------|---|---|---------------------------------------|
| RAL9003 Signal White (Gloss) | Matte White (Textured) | White (Textured) | | RAL7044 Silk Grey (Textured) |
| PT53 RAL7035 Light Grey (Textured) | PT54 RAL7037 Dusty Grey (Textured) | PT55 RAL7012 Basalt Grey (Textured) | PT56 RAL7016 Anthracite Grey (Textured) | PT11 Black (Textured) |
| PT57 | PT58 RAL8004 Copper Brown (Textured) | PT59 | PT60 | PT61 |
| RAL1015 Light Ivory (Textured) | | RAL6021 Pale Green (Textured) | RAL1019 Grey Beige (Textured) | RAL7006 Beige Grey (Textured) |
| PT62 RAL1003 Signal Yellow (Textured) | PT63 RAL3001 Signal Red (Textured) | PT64 RAL6001 Emerald Green (Textured) | PT65 RAL5005 Signal Blue (Textured) | PT66 RAL5003 Sapphire Blue (Textured) |

Metallic Paint Colors

| PT22 Platinum (Metallic Gloss) | PT48 Brass (Metallic Textured) | PT28 Dark Stainless (Metallic Gloss) | PT49 Bronze (Metallic Textured) | PT32 Dark Bronze (Metallic Gloss) | |
|--------------------------------|--------------------------------|--------------------------------------|------------------------------------|--------------------------------------|--|
| | | | | | |
| PT46 | | | | | |
| Aluminum (Metallic Textured) | | | | | |

Brushed Aluminum

| BAL | |
|------------------|--|
| Brushed Aluminum | |
| | |

Brushed Brass



Polished-Tinted Brass

| ATBR | DTBR | PBR | 1000 |
|----------------------|-------------------|----------------|------|
| Antique Tinted Brass | Dark Tinted Brass | Polished Brass | |
| | | | |

Plated Steel

| ANST | BBST | CPST | 1000 | PBST | SNST | |
|----------------------------|----------------------------|---------------------|------|-----------------------------|--------------------|--|
| Antique Brass Plated Steel | Brushed Brass Plated Steel | Chrome Plated Steel | | Polished Brass Plated Steel | Satin Nickel Steel | |
| | | | - | | | |

Polished Plated Brass

| CPBR | ALC: NO. | SNBR | |
|------------------------------|----------|---------------------------|--|
| Chrome Plated Polished Brass | | Satin Nickel Plated Brass | |
| | _ | | |

Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.

