# **INACTIVE SPEC SHEET**

Lisbon - Ceiling

AIC8783 33.50 in



JOB NAME: TYPE:

NOTES:

### **DESCRIPTION**

This classic collection offers the proven simplicity and purity of timeless geometry. When mid to high height ceiling applications present themselves, this luminaire delivers the style and performance to accomplish the tasks at hand.

### **FEATURES & BENEFITS**

- Opal acrylic diffuser lens enhances a space with filtered illumination
- Spun metal trim ring adds high-quality, decorative element to fixture
- · Handcrafted in USA

### **SPECIFICATIONS**


- LIGHT SOURCE: White LED light engine or incandescent
- LUMEN MAINTENANCE (LED): L70 = >50,000 Hrs.
- CCT: Available LED color temperatures: 3000K, 3500K, or 4000K
- DRIVER: LED versions feature integral Class II power supply standard
- **DIMMING:** 0-10V controls standard on LED light engines
- EMERGENCY: Emergency battery remote optional
- DIFFUSER: Opal acrylic is standard; matte acrylic and hand painted lenses optional
- **CONSTRUCTION:** Formed metal construction provides durable protection for internal components and is recyclable
- MOUNTING: Aluminum cover fits over a standard 4" octagonal junction box
- MODIFICATIONS: Consult factory for all modification requests
- APPROVALS: ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications







### **DIMENSIONS**




<b>W</b> 33.5 in 85.1 cm	<b>H</b> 10 in 25.4 cm	
unting W		
Approximate	e: 50 lb (23	3 kg)

### **CONFIGURATOR**

To configure your spec sheet online, go to <a href="https://www.spilighting.com/AIC8783">www.spilighting.com/AIC8783</a>. Not all options are available in all configurations; consult factory for details.

## Required Field \*



### A - LIGHT SOURCE \*

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

L86W | White 86W LED Light Engine

L43W | White 43W LED Light Engine

3N100 1 | 3INC100W/A19

See last page for finish options

<sup>1</sup> Incandescent Lamp(s) Not Included

# **B - VOLTAGE \***

120-277V | Universal Voltage

120V<sup>2</sup> | 120 Volt

<sup>2</sup> For incandescent light source only



## I AMP OPTIONS \*

5 - LAMP OPTIONS "
Delivered lumens shown are at 4000K CCT; apply multiplier for delivered lumens at other CCT.
☐ 3000K <sup>3</sup>   3000K CCT ☐ 3500K <sup>4</sup>   3500K CCT ☐ 4000K   4000K CCT
Apply .95 multiplier for delivered lumens
Apply .97 multiplier for delivered lumens
- DIFFUSER *
<ul> <li>□ DF_OA   Opal Acrylic Diffuser Lens (default)</li> <li>□ HP01   Silver Hand Painted Acrylic Diffuser</li> <li>□ HP02   Beige Hand Painted Acrylic Diffuser</li> <li>□ HP03   Amber Hand Painted Acrylic Diffuser</li> <li>□ MA01   Matte Acrylic Diffuser Lens</li> </ul>
OA HP01 HP02 HP03 MA01
- BOWL OPTIONS
FIN   Finial (See last page for finish options)
- OPTIONS

F | Fusing

## **Standard Finishes**

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing <a href="mailto:contact@spilighting.com">contact@spilighting.com</a>. Please note, finishes may not be available in all configurations.

### **Paint Colors**

PT01	PT51	PT02	PT04	PT11
RAL9003 Signal White (Gloss)	Matte White (Textured)	White (Textured)	RAL9001 Cream (Textured)	Black (Textured)

### **Metallic Paint Colors**

PT22	PT48	PT28	PT49	PT32	
Platinum (Metallic Gloss)	Brass (Metallic Textured)	Dark Stainless (Metallic Gloss)	Bronze (Metallic Textured)	Dark Bronze (Metallic Gloss)	
PT46					
Aluminum (Metallic Textured)					

### **Brushed Aluminum**



### **Brushed Brass**



### **Polished-Tinted Brass**

ATBR	DTBR	PBR	
Antique Tinted Brass	Dark Tinted Brass	Polished Brass	•

### **Plated Steel**



### **Polished Plated Brass**



# **Specialty Finishes**



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.