Paris - Pendant & Chandelier

AIP8485 33.20 in | (1) Bowl

JOB NAME:

NOTES:

TYPE:



DESCRIPTION

Our swept bowl collection offers unique styling and graceful lines. This low-profile series offers exceptional high-output lamping optics for low to mid-height ceiling applications. The family includes pendant, chandelier, wall-mounted, and ceiling models to illuminate and enhance the visual environment you`re creating.

FEATURES & BENEFITS

- Opal acrylic diffuser lens enhances a space with filtered illumination
- Spun metal trim ring adds high-quality, decorative element to fixture
- · Handcrafted in USA

SPECIFICATIONS


- LIGHT SOURCE: White LED light engine
- CRI: 80+ or 90+
- LUMEN MAINTENANCE: L70 = >50,000 Hrs.
- CCT: 2700K, 3000K, 3500K, 4000K, 5000K
- DRIVER: Integral Class 2 power supply standard
- DIMMING: 0-10V controls standard to 10% on LED light engines
- CONTROLS: Contact factory for control options (e.g., Lutron Athena, Current NX, nLight, Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- EMERGENCY: Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- **CONSTRUCTION:** Formed metal construction provides durable protection for internal components and is recyclable
- DIFFUSER: Opal acrylic is standard; matte acrylic and hand painted lenses optional. Any upward facing LEDs will be covered with a protective lens.
- MODIFICATIONS: Consult factory for all modification requests
- APPROVALS: ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications







DIMENSIONS



W	H	OAH	
33.2 in	6.2 in	42 in	
84.3 cm	15.7 cm	106.7 cm	
Mounting \	Veight		

Approximate: 50 lb (23 kg)

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/AIP8485. Not all options are available in all configurations; consult factory for details.

Required Field *



A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

L86W | White 86W LED Light Engine | Delivered Lumens: 8,475

L172W | White 172W LED Light Engine | Delivered Lumens: 16,950

See last page for finish options

B-VOLTAGE*

120-277V | Universal Voltage

C-LAMP OPTIONS*

Apply multiplier from chart for delivered lumens at other CCT's and CRI's.

2700K	2700K CC

3000К | 3000К ССТ

☐ **3500K** | 3500K CCT

☐ 4000K | 4000K CCT

■ 5000K | 5000K CCT

	80 CRI	90 CRI
2700K	1.00	0.84
3000K	1.00	0.84
3500K	1.00	0.84
4000K	1.00	0.84
5000K	1.00	0.84

D - CRI *

□ **DF_80** | (default)

90

E - DIFFUSER *


■ DF_OA | Opal Acrylic Diffuser Lens (default)

☐ **HP01** | Silver Hand Painted Acrylic Diffuser

HP02 | Beige Hand Painted Acrylic Diffuser

HP03 | Amber Hand Painted Acrylic Diffuser

MA01 | Matte Acrylic Diffuser Lens











F - MOUNTING *

Mounts to standard 4" octagonal junction box with auxiliary mounting holes. Additional support required (by others). Canopy features a 45 degree swivel.

DF_STM | Stem Mount (default)

G - EMERGENCY

10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.

EMR | Emergency Battery Remote

H-BOWL OPTIONS

FIN | Finial (See last page for finish options)

I - OPTIONS

KC01	Chain Kit (to	Transition Plate)	(See last nam	e for finish options

KR01 | Angled Stem Multi Kit (to Transition Plate) (See last page for finish options)

KS01 | Straight Stem Multi Kit (to Transition Plate) (See last page for finish options)

F | Fusing

¹ Not available in brass finishes.



J - OTHER THAN STANDARD OPTIONS

Specify overall height required from ceiling to the bottom of the fixture.

OAH | Pendant suspension length other than standard | Length:

Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

PT01 RAL9003 Signal White (Gloss)	PT51 Matte White (Textured)	PT02 White (Textured)	PT04 RAL9001 Cream (Textured)	PT67 RAL7044 Silk Grey (Textured)
PT53 RAL7035 Light Grey (Textured)	PT54 RAL7037 Dusty Grey (Textured)	PT55 RAL7012 Basalt Grey (Textured)	PT56 RAL7016 Anthracite Grey (Textured)	PT11 Black (Textured)
PT57 RAL1015 Light Ivory (Textured)	PT58 RAL8004 Copper Brown (Textured)	PT59 RAL6021 Pale Green (Textured)	PT60 RAL1019 Grey Beige (Textured)	PT61 RAL7006 Beige Grey (Textured)
PT62 RAL1003 Signal Yellow (Textured)	PT63 RAL3001 Signal Red (Textured)	PT64 RAL6001 Emerald Green (Textured)	PT65 RALS005 Signal Blue (Textured)	PT66 RAL5003 Sapphire Blue (Textured)

Metallic Paint Colors

PT22	PT48	PT28	PT49	PT32	
Platinum (Metallic Gloss)	Brass (Metallic Textured)	Dark Stainless (Metallic Gloss)	Bronze (Metallic Textured)	Dark Bronze (Metallic Gloss)	
PT46					
Aluminum (Motallic Textured)					

Brushed Aluminum

BAL	
Brushed Aluminum	

Brushed Brass



Polished-Tinted Brass

ATBR	DTBR	PBR	1000
Antique Tinted Brass	Dark Tinted Brass	Polished Brass	

Plated Steel

ANST		BBST	CPST	1000	PBST	1000	SNST	
Antique Brass Plated Steel		Brushed Brass Plated Steel	Chrome Plated Steel		Polished Brass Plated Steel		Satin Nickel Steel	
	A			_				

Polished Plated Brass

CPBR		SNBR	
Chrome Plated Polished Brass		Satin Nickel Plated Brass	
	-		DESCRIPTION OF THE PERSON OF T

Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.

