# Madrid - Ceiling

AIC8844 21.50 in

SPILIGHTING PROJECT DETAILS

JOB NAME:

TYPE:

NOTES:

#### DESCRIPTION

Our shallow bowl collection offers simple classic lines in a low-profile alternative. When low to mid-height ceiling applications present themselves, this family complements contemporary and transitional styling. The family includes pendant, chandelier, wall-mounted, and ceiling models to illuminate and enhance the visual environment you're creating.

#### FEATURES & BENEFITS

- Opal acrylic diffuser enhances a space with filtered illumination
- Spun metal trim ring adds high-quality, decorative element to fixture
- Optional finial available
- · Handcrafted in USA

#### **SPECIFICATIONS**

- LIGHT SOURCE: White LED light engine
- CRI: 80+ or 90+
- LUMEN MAINTENANCE: L70 = >50,000 Hrs.
- CCT: 2700K, 3000K, 3500K, 4000K, 5000K
- DRIVER: Integral Class 2 power supply standard
- DIMMING: 0-10V controls standard to 10% on LED light engines
- CONTROLS: Contact factory for control options (e.g., Lutron Athena, Current NX, nLight, Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- EMERGENCY: Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- DIFFUSER: Opal acrylic is standard; matte acrylic and hand painted lenses optional
- **CONSTRUCTION:** Formed metal construction provides durable protection for internal components and is recyclable
- **MOUNTING:** Aluminum cover fits over a standard 4" octagonal junction box
- MODIFICATIONS: Consult factory for all modification requests









 APPROVALS: ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

#### **DIMENSIONS**





W 21.5 in 5 in 54.6 cm 12.7 cm

Mounting Weight
Approximate: 25 lb (12 kg)

# **CONFIGURATOR**

To configure your spec sheet online, go to <a href="https://www.spilighting.com/AIC8844">www.spilighting.com/AIC8844</a>. Not all options are available in all configurations; consult factory for details.

# Required Field \*



#### A - LIGHT SOURCE \*

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

L22W | White 22W LED Light Engine | Delivered Lumens: 1,107

L43W | White 43W LED Light Engine | Delivered Lumens: 2,214

See last page for finish options

#### **B-VOLTAGE\***

☐ 120-277V | Universal Voltage

# **C-LAMP OPTIONS\***

Apply multiplier from chart for delivered lumens at other CCT's and CRI's.

2700K	2700K CC

**3000К |** 3000К ССТ

☐ **3500K** | 3500K CCT

☐ **4000K** | 4000K CCT

**■ 5000K |** 5000K CCT

	80 CRI	90 CRI
2700K	1.00	0.84
3000K	1.00	0.84
3500K	1.00	0.84
4000K	1.00	0.84
5000K	1.00	0.84

# D - CRI \*

**DF\_80** | (default)

90

# E - DIFFUSER \*

■ DF\_OA | Opal Acrylic Diffuser Lens (default)

☐ **HP01** | Silver Hand Painted Acrylic Diffuser

HP02 | Beige Hand Painted Acrylic Diffuser

HP03 | Amber Hand Painted Acrylic Diffuser

MA01 | Matte Acrylic Diffuser Lens











# F - EMERGENCY

10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.

**EMR** | Emergency Battery Remote

# **G-BOWL OPTIONS**

FIN | Finial

(See last page for finish options)

Н	- CANOPY
	SP   Canopy Spacer
ŀ	- OPTIONS
	F   Fusing



# **Standard Finishes**

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing <a href="mailto:contact@spilighting.com">contact@spilighting.com</a>. Please note, finishes may not be available in all configurations.

# **Paint Colors**

PT01 RAL9003 Signal White (Gloss)	PT51 Matte White (Textured)	PT02 White (Textured)	PT04 RAL9001 Cream (Textured)	PT67 RAL7044 Silk Grey (Textured)
PT53 RAL7035 Light Grey (Textured)	PT54 RAL7037 Dusty Grey (Textured)	PT55 RAL7012 Basalt Grey (Textured)	PT56 RAL7016 Anthracite Grey (Textured)	PT11 Black (Textured)
PT57 RAL1015 Light Ivory (Textured)	PT58 RAL8004 Copper Brown (Textured)	PT59 RAL6021 Pale Green (Textured)	PT60 RAL1019 Grey Beige (Textured)	PT61 RAL7006 Beige Grey (Textured)
PT62 RAL1003 Signal Yellow (Textured)	PT63 RAL3001 Signal Red (Textured)	PT64 RAL6001 Emerald Green (Textured)	PT65 RALS005 Signal Blue (Textured)	PT66 RAL5003 Sapphire Blue (Textured)

#### **Metallic Paint Colors**

PT22 Platinum (Metallic Gloss)	PT48 Brass (Metallic Textured)	PT28 Dark Stainless (Metallic Gloss)	PT49 Bronze (Metallic Textured)	PT32 Dark Bronze (Metallic Gloss)	
PT46					
Aluminum (Metallic Textured)					

#### **Brushed Aluminum**



#### **Brushed Brass**



#### **Polished-Tinted Brass**

ATBR	DTBR	PBR	1000
Antique Tinted Brass	Dark Tinted Brass	Polished Brass	

#### **Plated Steel**

ANST	BBST	CPST	1000	PBST	SNST	
Antique Brass Plated Steel	Brushed Brass Plated Steel	Chrome Plated Steel		Polished Brass Plated Steel	Satin Nickel Steel	
			_			

#### **Polished Plated Brass**

CPBR	10000	SNBR	
Chrome Plated Polished Brass		Satin Nickel Plated Brass	

# **Specialty Finishes**



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.

