

# INACTIVE SPEC SHEET

Ontario - Ceiling

AIC8918 29.00 in

**SPI**LIGHTING

PROJECT DETAILS

JOB NAME:

TYPE:

NOTES:

## DESCRIPTION

The ultra-thin circular housing creates a clean, floating appearance suitable for open office spaces, corridors, conference rooms and lobbies. Pendants, wall mounts, ADA sconces, and ceiling luminaires are all available within this family. Ontario's unique optical system provides an efficient indirect light solution with uniform ceiling brightness, even in low-ceiling spaces. The Ontario family is a versatile lighting alternative for demanding applications.

## FEATURES & BENEFITS

- Spun metal housing adds high-quality, decorative element to fixture
- Frosted acrylic shield enhances a space with diffused illumination
- Handcrafted in USA


## SPECIFICATIONS

- **LIGHT SOURCE:** White LED light engine
- **CRI:** 80+ (contact factory for 90+)
- **LUMEN MAINTENANCE:** L70 = >50,000 Hrs.
- **CCT:** 3000K, 3500K, or 4000K
- **DRIVER:** Integral Class 2 power supply standard
- **DIMMING:** 0-10V controls standard to 10% on LED light engines
- **EMERGENCY:** Emergency battery remote optional
- **MOUNTING:** Mounts to standard 4" octagonal junction box
- **MODIFICATIONS:** Consult factory for all modification requests
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications



EMR

DIMENSIONS



<b>W</b>	<b>H</b>
29 in	3.7 in
73.7 cm	9.4 cm
<b>Mounting Weight</b>	
Approximate: 50 lb (23 kg)	

CONFIGURATOR

To configure your spec sheet online, go to [www.spilighting.com/AIC8918](http://www.spilighting.com/AIC8918). Not all options are available in all configurations; consult factory for details.

Required Field \*

Catalog	Light Source*	Primary Finish*	Voltage*	Lamp Options*	Lens*	Options
AIC8918						
	A		B	C	D	E

A - LIGHT SOURCE \*

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

- ☐ **L29W** | White 29W LED Light Engine
- ☐ **L14W** | White 14W LED Light Engine

See last page for finish options

B - VOLTAGE \*

- ☐ **120-277V** | Universal Voltage

C - LAMP OPTIONS \*

Delivered lumens shown are at 4000K CCT; apply multiplier for delivered lumens at other CCT.


- ☐ **3000K**<sup>1</sup> | 3000K CCT
- ☐ **3500K**<sup>2</sup> | 3500K CCT
- ☐ **4000K** | 4000K CCT

<sup>1</sup> Apply .95 multiplier for delivered lumens

<sup>2</sup> Apply .97 multiplier for delivered lumens

D - LENS \*

- ☐ **DF\_AD01** | Flat Sandblasted Disk (default)
- ☐ **AD02** | Cone Disk
- ☐ **AD03** | Bowl Disk
- ☐ **GN** | Green Tint Clear Acrylic
- ☐ **OP** | Flat Opal Disk



E - OPTIONS

- ☐ **F** | Fusing

## Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing [contact@spilighting.com](mailto:contact@spilighting.com). Please note, finishes may not be available in all configurations.

### Paint Colors

<b>PT01</b> RAL9003 Signal White (Gloss)	<b>PT51</b> Matte White (Textured)	<b>PT02</b> White (Textured)	<b>PT04</b> RAL9001 Cream (Textured)	<b>PT11</b> Black (Textured)
---	---------------------------------------	---------------------------------	---	---------------------------------

### Metallic Paint Colors

<b>PT22</b> Platinum (Metallic Gloss)	<b>PT48</b> Brass (Metallic Textured)	<b>PT28</b> Dark Stainless (Metallic Gloss)	<b>PT49</b> Bronze (Metallic Textured)	<b>PT32</b> Dark Bronze (Metallic Gloss)
<b>PT46</b> Aluminum (Metallic Textured)				

## Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.