

INACTIVE SPEC SHEET

Oak

AIP11058 33.00 in

JOB NAME:

TYPE:

NOTES:

DESCRIPTION

An artful layered design reflects and highlights the uniquely formed pieces creating this stunning pendant. A frosted glass lens fully-encloses the light source, producing an internal glowing effect, while still supplying the space with ample supplemental illumination. This eye-catching piece is sure to make a statement.

FEATURES & BENEFITS


- Lamp source is not completely concealed, creating unique light patterns
- Chrome-plated accents add a unique, eye-catching element
- Optional uplight available
- Handcrafted in USA

SPECIFICATIONS

- **LIGHT SOURCE:** Incandescent
- **CONSTRUCTION:** Tempered glass lens protects lamp engine. Formed metal construction provides durable protection for internal components and is recyclable.
- **FINISH:** Choose from 26 standard thermoset polyester powder coat paint colors. RAL®, Pantone®, or custom finishes available upon request.
- **MODIFICATIONS:** Consult factory for all modification requests
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications



DIMENSIONS



W	H	OAH
33 in	33 in	81 in
83.8 cm	83.8 cm	205.7 cm
Mounting Weight		
Approximate: 50 lb (23 kg)		

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/AIP11058. Not all options are available in all configurations; consult factory for details.

Required Field *

Catalog	Light Source*	Primary Finish*	Voltage*	Light Source Option	Mounting*	Other Than Standard Options
AIP11058						
	A		B	C	D	E

A - LIGHT SOURCE *

☐ 1T100¹ | 1QTZ100W/T4/DC BAY

See last page for finish options

¹ Incandescent Lamp(s) Not Included

B - VOLTAGE *

☐ 120V | 120 Volt

C - LIGHT SOURCE OPTION

☐ 1F21 UL | (1) F21WT4/2D Uplight

D - MOUNTING *

Mounts to standard 4" octagonal junction box. Additional mounting structure and hardware required (by others). Field adjustable aircraft cables allow the fixture to be mounted at an application appropriate height (up to OAH). Power cord is white.

☐ DF_AC | Aircraft cable and power cord (default)

E - OTHER THAN STANDARD OPTIONS

Specify overall height required from ceiling to the bottom of the fixture.

OAH | Pendant suspension length other than standard

Length:

Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

PT01 RAL9003 Signal White (Gloss)	PT51 Matte White (Textured)	PT02 White (Textured)	PT04 RAL9001 Cream (Textured)	PT11 Black (Textured)
---	---------------------------------------	---------------------------------	---	---------------------------------

Metallic Paint Colors

PT22 Platinum (Metallic Gloss)	PT48 Brass (Metallic Textured)	PT28 Dark Stainless (Metallic Gloss)	PT49 Bronze (Metallic Textured)	PT32 Dark Bronze (Metallic Gloss)
PT46 Aluminum (Metallic Textured)				

Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.