INACTIVE SPEC SHEET

Lantern

AIP11579 29.00 in

JOB NAME: TYPE: NOTES:

DESCRIPTION

Transforming the classic cylinder by adding acrylic disks to form various shapes creates an open and clean look for the Lantern pendant. We offer four unique shapes to complement any space. The cylinder's matte acrylic option can add a soft glow of light to the space.

FEATURES & BENEFITS

- Opal acrylic diffuser lens enhances a space with filtered illumination
- 1/4" thick acrylic layered disks create a unique profile
- Each semi-translucent disk is screen printed with a circular design
- · Fixture supplied with opal acrylic bottom lens
- Handcrafted in USA

SPECIFICATIONS

- LIGHT SOURCE: White LED light engine
- CRI: 80+ (contact factory for 90+)
- LUMEN MAINTENANCE: L70 = >50,000 Hrs.
- CCT: 3000K, 3500K, or 4000K
- DRIVER: Integral Class 2 power supply standard
- DIMMING: 0-10V controls standard to 10% on LED light engines
- DIFFUSER: Opal acrylic


SPILIGHTING

- **FINISH:** Canopy, stem, top/bottom plate, the spacers between the lens and the flat caps are finished to match your specification. Choose from 26 standard thermoset polyester powder coat paint colors or various metal and plated finishes. RAL®, Pantone®, or custom finishes available upon request.
- MODIFICATIONS: Consult factory for all modification requests
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications





DIMENSIONS




W 29 in 73.7 cm	H 26 in 66 cm	OAH 42 in 106.7 cm			
Mounting Weight					
Approximate: 50 lb (23 kg)					

CONFIGURATOR

To configure your spec sheet online, go to <u>www.spilighting.com/AIP11579</u>. Not all options are available in all configurations; consult factory for details.

Required Field *



A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

L43W | White 43W LED Light Engine

See last page for finish options

B - VOLTAGE *

120-277V | Universal Voltage

C - LAMP OPTIONS *

Delivered lumens shown are at 4000K CCT; apply multiplier for delivered lumens at other CCT.

 3000K¹ | 3000K CCT

 3500K² | 3500K CCT

 4000K | 4000K CCT

Apply .95 multiplier for delivered lumens
 Apply .97 multiplier for delivered lumens



D - MOUNTING *

Mounts to standard 4" octagonal junction box with auxiliary mounting holes. Additional support required (by others). Canopy features a 45 degree swivel.

DF_STM | Stem Mount (default)

E - OTHER THAN STANDARD OPTIONS

Specify overall height required from ceiling to the bottom of the fixture.

OAH | Pendant suspension length other than standard Length:



Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing <u>contact@spilighting.com</u>. Please note, finishes may not be available in all configurations.

Paint Colors

PT01	PT51	PT02	PT04	PT11
RAL9003 Signal White (Gloss)	Matte White (Textured)	White (Textured)	RAL9001 Cream (Textured)	Black (Textured)

Metallic Paint Colors

PT22	PT48	PT28	PT49	PT32
Platinum (Metallic Gloss)	Brass (Metallic Textured)	Dark Stainless (Metallic Gloss)	Bronze (Metallic Textured)	Dark Bronze (Metallic Gloss)
PT46 Aluminum (Metallic Textured)				

Brushed Aluminum

ſ	BAL	
	Brushed Aluminum	

Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.

