

SPI LIGHTING

ECHO BLADE Micro Max

Exterior

Smallest | Most Powerful | Most Versatile



THE BASICS

Fixtures Remote 12448, Integral 12449, Soft 12450

Voltage 120-277V standard

Efficacy 102 lm/w

CRI 80+, 90+, 90+HE

CCT: 2700K, 3000K, 3500K, 4000K, 5000K

Dimming: 0-10V controls standard to 1%

Light Source: White LED light engine

Finish: Polished Aluminum
Brushed Aluminum
26 powder coat colors



Precision Optics
Remote



Precision Optics
Integral



Soft Optics
Remote/Integral

ECHO BLADE Micro Max Exterior

				MOUNTING OPTIONS	CRI OPTIONS	OPTICAL DISTRIBUTION	CATALOG NUMBER
DIRECT	PRECISION OPTICS		Remote	Mullion SCN	80 90	WA-Type IV	EEW 12448
			Integral	SSB	80	WA-Type IV	EEW 12449
	SOFT OPTICS		Remote	Mullion SSB	90+HE	Soft	EEW 12450
			Integral	Mullion SSB	90+HE	Soft	EEW 12450
INDIRECT	PRECISION OPTICS		Remote	Mullion SCN	80 90	WA-Type IV	EEW 12448
			Integral	SSB	80 90	WA-Type IV	EEW 12449

LUMEN DATA

Catalog ID	Driver	Wattage	Delivered Lumens
EEW12448	Remote	44	4479
	Remote	22	2240
	Remote	11	1120
EEW12449	Integral	44	4479
	Integral	22	2240
EEW12450	Integral/Remote-Mullion	28	2800
	Integral/Remote-Mullion	14	1400

