

SPI LIGHTING

LIGHTRUSS FOCUS

True Performance Optics | Glare Mitigation | Maximum Efficiency



THE BASICS

Sizes	24", 34" and 48"
Light Source	White LED light engine with gasketed and sealed LEDs
Lumen Maintenance	L90 >72,000 hrs @ 45° Ambient L90 >102,000 hrs @ 45° Ambient
Distributions	Indirect/Direct
Voltage	120-277V Standard
Efficacy	Up to 127 lm/W delivered
CRI	90+
CCT	3500K, 4000K, 5000K
Controls	Standard without controls. 0-10V, Lutron Athena, and nLight AIR optional. Contact factory for others.



Note:

Product data is for the fixture head only.


Each fixture attaches to a dual rail truss system with self-supporting geometry. The dual rail truss system is supported by fabricated bulk-heads which mount by either corrosion-resistant nickel alloy aircraft cables or stem. Contact factory for a full system layout.



LIGHTRUSS FOCUS


DIMENSIONS

LRU12455




W	H	L
18 in	4 in	24 in
45.7 cm	10.2 cm	61 cm

LRU12456




W	H	L
18 in	4 in	48 in
45.7 cm	10.2 cm	121.9 cm

LRU12457



W	H	L
18 in	4 in	34 in
45.7 cm	10.2 cm	86.4 cm

LRU12458



W	H	L
18 in	4 in	48 in
45.7 cm	10.2 cm	121.9 cm

LUMEN DATA - DIRECT/INDIRECT

Catalog ID	Size	Direct		Indirect	
		Wattage	Delivered Lumens	Wattage	Delivered Lumens
LRU12455	24"	83	9,628	216	27,388
LRU12457	34"	124	14,354	325	41,210
LRU12456	48"	83	9,628	739	93,273
LRU12458	48"	613	76,864	866	109,809