SPI LIGHTING

ZYNN 2" RING

THE BASICS

Distribution	Direct/Indirect
CCT	2700K, 3000k, 3500k, 4000k, 5000K
Voltage	120-277V standard
Efficacy	115 lm/w delivered
Controls	0-10V controls standard
CRI	80+ or 90+
Finishes	To specify separately, contact factory. Choose from 26 standard thermoset polyester powder coat paint colors or various metal finishes. RAL®, Pantone®, or custom finishes available upon request.

LUMEN DATA

Catalog ID	Diameter	DIRECT Wattage	DIRECT Delivered Lumens	INDIRECT Wattage	INDIRECT Delivered Lumens
AIP12203	26"	21	1,510	21	2,644
		42	3,020	42	5,288
		85	6,112	85	10,702
AIP12204	38"	32	2,301	32	4,029
		64	4,602	64	8,058
		127	9,131	127	15,989
AIP12205	50"	42	3,020	42	5,288
		85	6,112	85	10,702
		169	12,151	169	21,277
AIP12206	62"	53	3,811	53	6,673
		106	7,621	106	13,345
		212	15,243	212	26,691
AIP12207	74"	64	4,602	64	8,058
		127	9,131	127	15,989
		254	18,263	254	31,979
AIP12208	98"	85	6,112	85	10,702
		169	12,151	169	21,277
		339	24,374	339	42,680
AIP12209	122"	106	7,621	106	13,345
		212	15,243	212	26,691
		424	30,486	424	53,382
AIP12210	146"	127	9,131	127	15,989
		254	18,263	254	31,979
		508	36,525	508	63,957
AIP12211	194"	169	12,151	169	21,277
		339	24,374	339	42,680
		678	48,748	678	85,360