

Mounting Options

Tryg Linear

Surface Mount/Suspended


JOB NAME _____

TYPE _____


MOSR FBK - Surface Mount

Fixed Bracket

- Remote Power Supply
- Bracket painted to match fixture
- Compliant with Disabilities Act (ADA) requirements
- Adjustable mounting points




Detail View



NON POWER

- Mounts to most surfaces and materials
- Suitable blocking required (by others)




POWER

- Mounts to most surfaces and materials
- Suitable blocking required (by others)
- Supplied with six feet of black power cord to allow j-box connections (by others) in an inconspicuous and accessible place


BUL - Adjustable Mounting Points

.6" x .8" Ceiling Coupler

- Remote Power Supply
- Nickel-plated ceiling coupler is .6" in diameter and is .8" high
- Mounts to most surfaces and materials
- Mountable on any sloped ceiling or even walls with 0-90° mounting ability




Detail View



NON POWER

- Mounts to structure with appropriate #8 screw by others or over a 1/4-20 stud by others. Suitable blocking required (by others)
- Braided aircraft cable provides full vertical field adjustment at the fixture
- Does not require j-box for mounting



POWER

- Mounts to supported 4" octagonal j-box (by others) with crossbar and ceiling coupler
- Braided aircraft cable provides full vertical field adjustment at the fixture
- 5" canopy and is .2" high and white unless otherwise specified


Black power cord and white canopy supplied unless otherwise specified.

White power cord


CAA - Adjustable Mounting Points

5" Canopy and Aircraft Cable

- Remote Power Supply
- Nickel-plated ceiling coupler is .6" in diameter and is .8" high
- 5" canopy is .2" high and white unless otherwise specified
- Mountable on any sloped ceiling or even walls with 0-90° mounting ability




Detail View



NON POWER

- Mounts to supported 4" octagonal j-box (by others) with crossbar and ceiling coupler
- Braided aircraft cable provides vertical field adjustment at the fixture



POWER

- Mounts to supported 4" octagonal j-box (by others) with crossbar and ceiling coupler
- Braided aircraft cable provides vertical field adjustment at the fixture


Black power cord and white canopy supplied unless otherwise specified.

White power cord


CAS - For Non-Accessible Ceilings

5" Canopy and Stem

- Remote Power Supply
- Canopy and stem painted to match the fixture
- 5" canopy covers standard 4" octagonal j-box (supplied by others)
- 15° swivel




Detail View



NON POWER

- Mounts to standard 4" octagonal j-box (by others)
- Suitable blocking required (by others)



POWER

- Mounts to standard 4" octagonal j-box (by others)
- Suitable blocking required (by others)
- Power wires concealed inside stem