Cubes - Ceiling

AIC11990 25.00 in

SPILIGHTING PROJECT DETAILS

JOB NAME: TYPE:

NOTES:

DESCRIPTION

Combining clean, geometric shapes to create luminous forms, the Cubes family is a guaranteed way to make a powerful design statement. Cubes are individually hand fabricated with highly transmissive matte opal acrylic diffusers. Utilizing long-lasting LEDs, these fixtures are energy efficient while maintaining a uniformly illuminated body. Available in ceiling and pendant mounts, Cubes are perfectly suited for your contemporary setting.

SPECIFICATIONS

• LIGHT SOURCE: White LED light engine

• CRI: 90+HE

• LUMEN MAINTENANCE: L70 = >50,000 Hrs.

• CCT: 2700K, 3000K, 3500K, 4000K, 5000K

• VOLTAGE: 120-277V standard

• DRIVER: Integral Class 2 power supply

• **DIMMING:** 0-10V controls standard to 1% on LED light engines

- **CONTROLS:** Contact factory for control options (e.g., Lutron Athena, Current NX, nLight, Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- EMERGENCY: Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- MOUNTING: Mounts to standard 4" octagonal junction box
- APPROVALS: ETL listed to UL standards (US and Canada) for use in damp locations; not recommended for exterior applications















DIMENSIONS





N 25 in 53.5 cm	H 13.7 in 34.8 cm	
3.5 cm lounting W		
-	-	
Consult Fac	torv.	

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/AIC11990. Not all options are available in all configurations; consult factory for details.

Required Field *



A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application. Alternative wattages available upon request.

L57W White 57W LED Light	ht Engine	Delivered Lumens: 4,843
L115W White 115W LED L	ight Engine	Delivered Lumens: 9,687
Cust_Out		
Lumen Calculator: Enter	Lumens or W	atts if different than displayed
	LU M	lin 4822 - Max 9729
	W	lin 57 0 - May 115 0

See last page for finish options

*For requests outside Min-Max range, please contact factory.

B-VOLTAGE*

☐ 120-277V | Universal Voltage

C - LAMP OPTIONS *
Apply multiplier from chart for delivered lumens at other CCT's and CRI's.
☐ 2700K 2700K CCT
☐ 3000K 3000K CCT
☐ 4000K 4000K CCT
D - CRI *
☐ DF_90+HE 90+ High Efficacy
E - EMERGENCY
10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.
☐ EMR Emergency Battery Remote



Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

PT01	PT51	PT02	PT04 RAL9001 Cream (Textured)	PT67
RAL9003 Signal White (Gloss)	Matte White (Textured)	White (Textured)		RAL7044 Silk Grey (Textured)
PT53 RAL7035 Light Grey (Textured)	PT54 RAL7037 Dusty Grey (Textured)	PT55 RAL7012 Basalt Grey (Textured)	PT56 RAL7016 Anthracite Grey (Textured)	PT11 Black (Textured)
PT57	PT58 RAL8004 Copper Brown (Textured)	PT59	PT60	PT61
RAL1015 Light Ivory (Textured)		RAL6021 Pale Green (Textured)	RAL1019 Grey Beige (Textured)	RAL7006 Beige Grey (Textured)
PT62 RAL1003 Signal Yellow (Textured)	PT63 RAL3001 Signal Red (Textured)	PT64 RAL6001 Emerald Green (Textured)	PT65 RAL5005 Signal Blue (Textured)	PT66 RAL5003 Sapphire Blue (Textured)

Metallic Paint Colors

PT22	PT48	PT28	PT49	PT32
Platinum (Metallic Gloss)	Brass (Metallic Textured)	Dark Stainless (Metallic Gloss)	Bronze (Metallic Textured)	Dark Bronze (Metallic Gloss)
PT46				
Aluminum (Metallic Textured)				

Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.