# Stockholm - Ceiling

AIC8778 21.50 in

JOB NAME:

NOTES:

TYPE:



#### **DESCRIPTION**

Stockholm is part of our classic bowl collection, hallmarked by the proven simplicity and purity of timeless geometry. It features a deeper shape ideal for mid to high height ceiling applications. The family includes pendant, chandelier, wall-mounted, and ceiling models to illuminate and enhance the visual environment.

#### **FEATURES & BENEFITS**

- Opal acrylic diffuser lens enhances a space with filtered illumination
- Spun metal trim ring adds high-quality, decorative element to fixture
- · Handcrafted in USA

#### **SPECIFICATIONS**

- LIGHT SOURCE: White LED light engine or incandescent
- CRI: 90+HE
- Lumen Maintenance: L70 = >50,000 Hrs.
- CCT: Available LED color temperatures: 2700K, 3000K, 3500K, 4000K, 5000K
- DRIVER: LED versions feature integral Class 2 power supply standard
- **DIMMING:** 0-10V controls standard to 10% on LED light engines
- **CONTROLS:** Contact factory for control options (e.g., Lutron Athena, Current NX, nLight, Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- EMERGENCY: Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- DIFFUSER: Opal acrylic is standard; matte acrylic and hand painted lenses optional
- **CONSTRUCTION:** Formed metal construction provides durable protection for internal components and is recyclable
- **MOUNTING:** Aluminum cover fits over a standard 4" octagonal junction box












- MODIFICATIONS: Consult factory for all modification requests
- APPROVALS: ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

#### **DIMENSIONS**



| <b>W</b> | <b>H1</b> | <b>H2</b> |
|----------|-----------|-----------|
| 21.5 in  | 9.2 in    | 11.2 in   |
| 54.6 cm  | 23.4 cm   | 28.4 cm   |

Mounting Weight Approximate: 25 lb (12 kg)

### **CONFIGURATOR**

To configure your spec sheet online, go to <a href="https://www.spilighting.com/AIC8778">www.spilighting.com/AIC8778</a>. Not all options are available in all configurations; consult factory for details.

#### Required Field \*

| Catalog | Light Source* | Primary Finish* | Voltage* | Lamp Options* | CRI* | Diffuser* | Emergency | Bowl Options | Canopy | Options |
|---------|---------------|-----------------|----------|---------------|------|-----------|-----------|--------------|--------|---------|
| AIC8778 |               |                 |          |               |      |           |           |              |        |         |
|         |               |                 |          |               |      |           |           | Finish:      |        |         |
|         |               | Д               | В        | C             | D    | E         | F         | G            | Н      | 1       |

#### A - LIGHT SOURCE \*

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

| L29W    | White 29W L  | ED Light Engi | ine    | Delivered Lumens: 1,476           |
|---------|--------------|---------------|--------|-----------------------------------|
| L57W    | White 57W L  | ED Light Engi | ine    | Delivered Lumens: 2,952           |
| □ 3N60  | 1   3INC60W/ | <b>A</b> 19   |        |                                   |
| Cust_0  | ut           |               |        |                                   |
| Lumen ( | Calculator:  | Enter Lume    | ens or | Watts if different than displayed |
|         |              |               | LU     | Min 1479 - Max 2907               |
|         |              |               | W      | Min 29.0 - Max 57.0               |

See last page for finish options



<sup>1</sup> Incandescent Lamp(s) Not Included \*For requests outside Min-Max range, please contact factory.

| 3 - VOLTAGE *   |
|---|
| ☐ 120-277V   Universal Voltage ☐ 120V <sup>2</sup>   120 Volt   |
| For incandescent light source only  |
| : - LAMP OPTIONS *  |
| Apply multiplier from chart for delivered lumens at other CCT's and CRI's. Not required with incandescent.  |
| <ul> <li>         □ 2700K   2700К ССТ         □ 3000К   3000К ССТ         □ 3500K   3500К ССТ         □ 4000К   4000К ССТ         □ 5000К   5000К ССТ         □</li> </ul>  |
| ) - CRI *   |
| ☐ DF_90+HE   90+ High Efficacy  |
| - DIFFUSER *  |
| <ul> <li>□ DF_OA   Opal Acrylic Diffuser Lens (default)</li> <li>□ HP01   Silver Hand Painted Acrylic Diffuser</li> <li>□ HP02   Beige Hand Painted Acrylic Diffuser</li> <li>□ HP03   Amber Hand Painted Acrylic Diffuser</li> <li>□ MA01   Matte Acrylic Diffuser Lens</li> </ul> |
| OA HP01 HP02 HP03 MA01  |
| - EMERGENCY   |
| 10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.  |
| ☐ EMR   Emergency Battery Remote  |
| G - BOWL OPTIONS  |
| FIN   Finial (See last page for finish options)   |

| Н | - CANOPY           |
|---|--------------------|
|   | SP   Canopy Spacer |
| ŀ | - OPTIONS          |
|   | F   Fusing         |



## **Standard Finishes**

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing <a href="mailto:contact@spilighting.com">contact@spilighting.com</a>. Please note, finishes may not be available in all configurations.

## **Paint Colors**

| PT01  | PT51                                 | PT02                                      | PT04 RAL9001 Cream (Textured)           | PT67                                  |
|---|--------------------------------------|---|---|---------------------------------------|
| RAL9003 Signal White (Gloss)                | Matte White (Textured)               | White (Textured)                          |   | RAL7044 Silk Grey (Textured)          |
| PT53<br>RAL7035 Light Grey (Textured)       | PT54 RAL7037 Dusty Grey (Textured)   | PT55<br>RAL7012 Basalt Grey<br>(Textured) | PT56 RAL7016 Anthracite Grey (Textured) | PT11<br>Black (Textured)              |
| PT57  | PT58 RAL8004 Copper Brown (Textured) | PT59                                      | PT60                                    | PT61                                  |
| RAL1015 Light Ivory (Textured)              |                                      | RAL6021 Pale Green (Textured)             | RAL1019 Grey Beige (Textured)           | RAL7006 Beige Grey (Textured)         |
| PT62<br>RAL1003 Signal Yellow<br>(Textured) | PT63 RAL3001 Signal Red (Textured)   | PT64 RAL6001 Emerald Green (Textured)     | PT65 RAL5005 Signal Blue (Textured)     | PT66 RAL5003 Sapphire Blue (Textured) |

#### **Metallic Paint Colors**

| PT22<br>Platinum (Metallic Gloss) | PT48 Brass (Metallic Textured) | PT28 Dark Stainless (Metallic | Gloss) | PT49<br>Bronze (Metallic Textured) | PT32<br>Dark Bronze (Metallic Gloss) |  |
|-----------------------------------|--------------------------------|-------------------------------|--------|------------------------------------|--------------------------------------|--|
| PT46 Aluminum (Metallic Textured) |                                |                               |        |                                    |                                      |  |

#### **Brushed Aluminum**

| BAL              |  |
|------------------|--|
| Brushed Aluminum |  |
|                  |  |

#### **Brushed Brass**



### **Polished-Tinted Brass**

| ATBR                 | DTBR              | PBR            |  |
|----------------------|-------------------|----------------|--|
| Antique Tinted Brass | Dark Tinted Brass | Polished Brass |  |
|                      |                   |                |  |

## **Plated Steel**

| ANST                       | BBST                       | CPST                | 100 | PBST                        |   | SNST               |  |
|----------------------------|----------------------------|---------------------|-----|-----------------------------|---|--------------------|--|
| Antique Brass Plated Steel | Brushed Brass Plated Steel | Chrome Plated Steel | -   | Polished Brass Plated Steel |   | Satin Nickel Steel |  |
|                            |                            |                     | _   |                             | _ |                    |  |

#### **Polished Plated Brass**

| CPBR                         | SNBR                      |  |
|------------------------------|---------------------------|--|
| Chrome Plated Polished Brass | Satin Nickel Plated Brass |  |



# **Specialty Finishes**



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.

