

# OUTLINES Pendant

AIP12478 2.00 in | PENTAGON

JOB NAME:

TYPE:

NOTES:

## DESCRIPTION

PENTAGON- DIRECT

### FEATURES & BENEFITS

- Seamless lens
- Canopy shape matches fixture shape
- Seamless housing is finished to your specification
- Sleek 2" x 3" profile
- Clean, continuous lines of light with zero pixelation
- Superior fit and finish
- Keep ceilings clean with minimal mounting hardware
- Hidden internal aircraft cable grippers are easy to adjust
- Handcrafted in USA, BABA Compliant



### SPECIFICATIONS

- **LIGHT SOURCE:** White LED light engine
- **DISTRIBUTION:** Direct
- **CRI:** 90+HE
- **LUMEN MAINTENANCE:** TBD
- **EFFICACY:** Estimated 72 lm/w delivered
- **CCT:** 2700K, 3000K, 3500K, 4000K, 5000K
- **VOLTAGE:** 120-277V standard
- **MAX AMBIENT OPERATING TEMP:** TBD
- **DIMMING:** 1% minimum dim level standard
- **CONTROLS:** 0-10V standard. Lutron Athena, Current NX, and nLight AIR optional. Contact factory for other controls (e.g., Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- **EMERGENCY:** Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- **INTEGRATED SURGE PROTECTION:** LED components are protected against minor surge events
- **DIFFUSER:** Seamless matte opal acrylic (bottom). Frosted clear acrylic (top).



- **CONSTRUCTION:** Housing fabricated from 6000 series aluminum extrusion
- **FINISH:** Housing and mounting components finished to match. To specify separately, contact factory. Choose from 26 standard thermoset polyester powder coat paint colors or various metal finishes. RAL®, Pantone®, or custom finishes available upon request.
- **MODIFICATIONS:** Consult factory for all modification requests, including alternate sizes
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

## DIMENSIONS



2FT	D	L	W	H	OAH
	24.2 in 61.5 cm	21.9 in 55.6 cm	23.1 in 58.7 cm	3 in 7.6 cm	48 in 121.9 cm

Mounting Weight: Consult Factory.

3FT	D	L	W	H	OAH
	36.1 in 91.7 cm	32.6 in 82.8 cm	34.3 in 87.1 cm	3 in 7.6 cm	48 in 121.9 cm

Mounting Weight: Consult Factory.

4FT	D	L	W	H	OAH
	48 in 121.9 cm	43.4 in 110.2 cm	45.6 in 115.8 cm	3 in 7.6 cm	48 in 121.9 cm

Mounting Weight: Consult Factory.

## CONFIGURATOR

To configure your spec sheet online, go to [www.spilighting.com/AIP12478](http://www.spilighting.com/AIP12478). Not all options are available in all configurations; consult factory for details.

### Required Field \*

Catalog AIP12478	Light Source*	Primary Finish*	Voltage*	Lamp Options*	CRI*	Controls	Mounting*	Emergency	Canopy*	Options	Other Than Standard Options
	A		B	C	D	E	F	G	H	I	J

## A - LIGHT SOURCE \*

---

### 2 FOOT NOMINAL FIXTURE

- DIR-L35W** | White 35W LED Light Engine | Delivered Lumens: 2,520
- DIR-L71W** | White 71W LED Light Engine | Delivered Lumens: 5,112

### 3 FOOT NOMINAL FIXTURE

- DIR-L53W** | White 53W LED Light Engine | Delivered Lumens: 3,816
- DIR-L106W** | White 106W LED Light Engine | Delivered Lumens: 7,632

### 4 FOOT NOMINAL FIXTURE

- DIR-L70W** | White 70W LED Light Engine
- DIR-L141W** | White 141W LED Light Engine | Delivered Lumens: 10,152

See last page for finish options

## B - VOLTAGE \*

---

- 120-277V | Universal Voltage

## C - LAMP OPTIONS \*

---

- 2700K | 2700K CCT
- 3000K | 3000K CCT
- 3500K | 3500K CCT
- 4000K | 4000K CCT
- 5000K | 5000K CCT

## D - CRI \*

---

- 90+HE | 90+ High Efficacy

## E - CONTROLS

---

- DF\_DIM1 | 0-10V Control, 1% Dimming (default)
- AWRN | Lutron Athena Wireless Node, 1% Dimming
- NX | Current NX Wireless, 1% Dimming
- NLTA | Acuity nLight Air, 1% Dimming

## F - MOUNTING \*

---

- MIA | Canopy (default)
- SIA | Straight Aircraft Cables and Power Cord, Integral Supply

## G - EMERGENCY

---

- EMR | Emergency Battery Remote

## H - CANOPY \*

---

- DF\_SRC | Standard 6" Round Canopy
- CMF | Canopy Matches Fixture Shape

## I - OPTIONS

---

- BPC | Black Power Cord

## J - OTHER THAN STANDARD OPTIONS

---

OAH | Pendant suspension length other than standard Length:

## Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing [contact@spilighting.com](mailto:contact@spilighting.com). Please note, finishes may not be available in all configurations.

### Paint Colors

<b>PT01</b> RAL9003 Signal White (Gloss)	<b>PT51</b> Matte White (Textured)	<b>PT02</b> White (Textured)	<b>PT04</b> RAL9001 Cream (Textured)	<b>PT67</b> RAL7044 Silk Grey (Textured)
<b>PT53</b> RAL7035 Light Grey (Textured)	<b>PT54</b> RAL7037 Dusty Grey (Textured)	<b>PT55</b> RAL7012 Basalt Grey (Textured)	<b>PT56</b> RAL7016 Anthracite Grey (Textured)	<b>PT11</b> Black (Textured)
<b>PT57</b> RAL1015 Light Ivory (Textured)	<b>PT58</b> RAL8004 Copper Brown (Textured)	<b>PT59</b> RAL6021 Pale Green (Textured)	<b>PT60</b> RAL1019 Grey Beige (Textured)	<b>PT61</b> RAL7006 Beige Grey (Textured)
<b>PT62</b> RAL1003 Signal Yellow (Textured)	<b>PT63</b> RAL3001 Signal Red (Textured)	<b>PT64</b> RAL6001 Emerald Green (Textured)	<b>PT65</b> RAL5005 Signal Blue (Textured)	<b>PT66</b> RAL5003 Sapphire Blue (Textured)

### Metallic Paint Colors

<b>PT22</b> Platinum (Metallic Gloss)	<b>PT48</b> Brass (Metallic Textured)	<b>PT28</b> Dark Stainless (Metallic Gloss)	<b>PT49</b> Bronze (Metallic Textured)	<b>PT32</b> Dark Bronze (Metallic Gloss)
<b>PT46</b> Aluminum (Metallic Textured)				

## Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.