

# OUTLINES

AIP12480 2.00 in | HEXAGON

JOB NAME:

TYPE:

NOTES:

## DESCRIPTION

HEXAGON- DIRECT

### FEATURES & BENEFITS

- Seamless lens
- Canopy shape matches fixture shape
- Seamless housing is finished to your specification
- Sleek 2" x 3" profile
- Clean, continuous lines of light with zero pixelation
- Superior fit and finish
- Keep ceilings clean with minimal mounting hardware
- Hidden internal aircraft cable grippers are easy to adjust
- Handcrafted in USA, BABA Compliant

### SPECIFICATIONS



- **LIGHT SOURCE:** White LED light engine
- **DISTRIBUTION:** Direct
- **CRI:** 80+ or 90+
- **LUMEN MAINTENANCE:** L80 = >60,000 Hrs.
- **EFFICACY:** Up to 115 lm/W delivered
- **CCT:** 2700K, 3000K, 3500K, 4000K, 5000K
- **VOLTAGE:** 120-277V standard
- **DRIVER:** Remote Class 2 power supply. Max distance to the driver (including OAH) is: #18 AWG = 50', #16 AWG = 75', #14 AWG = 100'. For extended distances, contact factory.
- **MAX AMBIENT OPERATING TEMP:** 42°C (108°F)
- **DIMMING:** 1% minimum dim level standard
- **CONTROLS:** 0-10V standard. Lutron Athena, Current NX, and nLight AIR optional. Contact factory for other controls (e.g., Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- **EMERGENCY:** Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- **INTEGRATED SURGE PROTECTION:** LED components are



protected against minor surge events

- **DIFFUSER:** Seamless matte opal acrylic (bottom). Frosted clear acrylic (top).
- **CONSTRUCTION:** Housing fabricated from 6000 series aluminum extrusion
- **FINISH:** Housing and mounting components finished to match. To specify separately, contact factory. Choose from 26 standard thermoset polyester powder coat paint colors or various metal finishes. RAL®, Pantone®, or custom finishes available upon request.
- **MODIFICATIONS:** Consult factory for all modification requests, including alternate sizes
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

## DIMENSIONS



2FT	<b>D</b>	<b>L</b>	<b>W</b>	<b>OAH</b>
	24.4 in 62 cm	24.4 in 62 cm	21.1 in 53.6 cm	60 in 152.4 cm

Mounting Weight: Consult Factory.

3FT	<b>D</b>	<b>L</b>	<b>W</b>	<b>OAH</b>
	36.4 in 92.5 cm	36.4 in 92.5 cm	31.5 in 80 cm	60 in 152.4 cm

Mounting Weight: Consult Factory.

4FT	<b>D</b>	<b>L</b>	<b>W</b>	<b>OAH</b>
	48 in 121.9 cm	48 in 121.9 cm	41.6 in 105.7 cm	60 in 152.4 cm

Mounting Weight: Consult Factory.

## CONFIGURATOR

To configure your spec sheet online, go to [www.spilighting.com/AIP12480](http://www.spilighting.com/AIP12480). Not all options are available in all configurations; consult factory for details.

### Required Field \*

Catalog AIP12480	Light Source*	Primary Finish*	Voltage*	Lamp Options	CRI*	Controls*	Mounting*	Emergency	Options	Other Than Standard Options
	A	B	C	D	E	F	G	H	I	

## A - LIGHT SOURCE \*

---

### 2 FOOT NOMINAL FIXTURE

- DIR-L36W** | White 36W LED Light Engine | Delivered Lumens: 12,800
- DIR-L73W** | White 73W LED Light Engine | Delivered Lumens: 19,200

### 3 FOOT NOMINAL FIXTURE

- DIR-L54W** | White 54W LED Light Engine | Delivered Lumens: 14,400
- DIR-L109W** | White 109W LED Light Engine | Delivered Lumens: 19,200

### 4 FOOT NOMINAL FIXTURE

- DIR-L72W** | White 72W LED Light Engine | Delivered Lumens: 5,184
- DIR-L145W** | White 145W LED Light Engine | Delivered Lumens: 10,440

See last page for finish options

## B - VOLTAGE \*

---

- 120-277V | Universal Voltage

## C - LAMP OPTIONS

---

- 2700K | 2700K CCT
- 3000K | 3000K CCT
- 3500K | 3500K CCT
- 4000K | 4000K CCT
- 5000K | 5000K CCT

## D - CRI \*

---

- DF\_80 | (default)
- 90

## E - CONTROLS \*

---

- DF\_DIM1 | 0-10V Control, 1% Dimming (default)
- NX | Current NX Wireless, 1% Dimming
- NLTA | Acuity nLight Air, 1% Dimming

## F - MOUNTING \*

---

- DF\_MIA | Canopy (default)
- SIA | Straight Aircraft Cables and Power Cord, Integral Supply

## G - EMERGENCY

---

- EMR | Emergency Battery Remote

**H - OPTIONS**

---

BPC | Black Power Cord

**I - OTHER THAN STANDARD OPTIONS**

---

OAH | Pendant suspension length other than standard Length:

## Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing [contact@spilighting.com](mailto:contact@spilighting.com). Please note, finishes may not be available in all configurations.

### Paint Colors

<b>PT01</b> RAL9003 Signal White (Gloss)	<b>PT51</b> Matte White (Textured)	<b>PT02</b> White (Textured)	<b>PT04</b> RAL9001 Cream (Textured)	<b>PT67</b> RAL7044 Silk Grey (Textured)
<b>PT53</b> RAL7035 Light Grey (Textured)	<b>PT54</b> RAL7037 Dusty Grey (Textured)	<b>PT55</b> RAL7012 Basalt Grey (Textured)	<b>PT56</b> RAL7016 Anthracite Grey (Textured)	<b>PT11</b> Black (Textured)
<b>PT57</b> RAL1015 Light Ivory (Textured)	<b>PT58</b> RAL8004 Copper Brown (Textured)	<b>PT59</b> RAL6021 Pale Green (Textured)	<b>PT60</b> RAL1019 Grey Beige (Textured)	<b>PT61</b> RAL7006 Beige Grey (Textured)
<b>PT62</b> RAL1003 Signal Yellow (Textured)	<b>PT63</b> RAL3001 Signal Red (Textured)	<b>PT64</b> RAL6001 Emerald Green (Textured)	<b>PT65</b> RAL5005 Signal Blue (Textured)	<b>PT66</b> RAL5003 Sapphire Blue (Textured)

### Metallic Paint Colors

<b>PT22</b> Platinum (Metallic Gloss)	<b>PT48</b> Brass (Metallic Textured)	<b>PT28</b> Dark Stainless (Metallic Gloss)	<b>PT49</b> Bronze (Metallic Textured)	<b>PT32</b> Dark Bronze (Metallic Gloss)
<b>PT46</b> Aluminum (Metallic Textured)				

## Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.