INACTIVE SPEC SHEET

Homestead

AIP8170 39.00 in



JOB NAME: TYPE:

NOTES:

DESCRIPTION

A shallow formed opal acrylic bowl and a 45 degree flared trim ring offer a slightly more contemporary look to the Homestead pendant, making it perfect for retail spaces, contemporary conference areas, and public buildings. Choose from a palette of both painted and metal trim finishes.

FEATURES & BENEFITS

- Opal acrylic diffuser lens enhances a space with filtered illumination.
- Handcrafted in USA


SPECIFICATIONS

- LIGHT SOURCE: White LED light engine or incandescent
- CRI: 80+ (contact factory for 90+)
- Lumen Maintenance: L70 = >50,000 Hrs.
- CCT: Available LED color temperatures: 3000K, 3500K, or 4000K
- DRIVER: LED versions feature integral Class 2 power supply standard
- **DIMMING:** 0-10V controls standard to 10% on LED light engines
- EMERGENCY: Emergency battery remote optional
- DIFFUSER: Opal acrylic is standard; matte acrylic and hand painted lenses optional. Any upward facing LEDs will be covered with a protective lens.
- MODIFICATIONS: Consult factory for all modification requests
- APPROVALS: ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications





DIMENSIONS



W	H	OAH				
39 in	10 in	36 in				
99.1 cm	25.4 cm	91.4 cm				
Mounting Woight						

Mounting Weight
Approximate: 50 lb (23 kg)

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/AIP8170. Not all options are available in all configurations; consult factory for details.

Required Field *



A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

L57W | White 57W LED Light Engine

L115W | White 115W LED Light Engine

8N100 1 | 8INC100W/A19

See last page for finish options

¹ Incandescent Lamp(s) Not Included

B - VOLTAGE *

120-277V | Universal Voltage

☐ 120V ² | 120 Volt

² For incandescent light source only



C-LAMP OPTIONS* Delivered lumens shown are at 4000K CCT; apply multiplier for delivered lumens at other CCT. ☐ 3000K ³ | 3000K CCT ☐ 4000K | 4000K CCT ³ Apply .95 multiplier for delivered lumens ⁴ Apply .97 multiplier for delivered lumens **D - DIFFUSER *** ☐ DF_OA | Opal Acrylic Diffuser Lens (default) ☐ HP01 | Silver Hand Painted Acrylic Diffuser ☐ HP02 | Beige Hand Painted Acrylic Diffuser ☐ HP03 | Amber Hand Painted Acrylic Diffuser MA01 | Matte Acrylic Diffuser Lens **MA01** OA HP01 HP02 HP03 **E - MOUNTING *** Mounts to standard 4" octagonal junction box with auxiliary mounting holes. Additional support required (by others). ☐ DF_STM | Stem Mount (default) F - BOWL OPTIONS FIN | Finial (See last page for finish options)

SPILIGHTING

G-CANOPY

H-OPTIONS

SAM45 | 45 Degree Swivel

KA03 | Aircraft Cable Stem Kit to Transition Plate and Canopy

(See last page for finish options)

(See last page for finish options)



I - OTHER THAN STANDARD OPTIONS

Specify overall height required from ceiling to the bottom of the fixture.

OAH | Pendant suspension length other than standard | Length:



Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

PT01	PT51	PT02	PT04	PT11
RAL9003 Signal White (Gloss)	Matte White (Textured)	White (Textured)	RAL9001 Cream (Textured)	Black (Textured)

Metallic Paint Colors



Brushed Aluminum



Brushed Brass



Polished-Tinted Brass

ATBR	DTBR	PBR	1000
Antique Tinted Brass	Dark Tinted Brass	Polished Brass	

Polished Plated Brass



Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.