# Minsk - Pendant & Chandelier

AIP8533 29.00 in | (1) Bowl

SPI LIGHTING
PROJECT DETAILS

JOB NAME:
TYPE:
NOTES:

## DESCRIPTION

Our drum collection was inspired to create something different and new in the world of luminous lighting products, yet we find this simple form offers classic lines and patterns. Its application can approach a broad array of architectural environments for a new and fresh approach without losing its appeal in the years to come. The family includes pendant, chandelier, wall-mounted, and ceiling models to illuminate and enhance environments where you are looking to break stride with the past.

FEATURES & BENEFITS

- Opal acrylic diffuser lens enhances a space with filtered illumination
- Spun metal trim ring adds high-quality, decorative element to fixture
- Optional finial available
- Handcrafted in USA

SPECIFICATIONS

- **LIGHT SOURCE:** White LED light engine or incandescent
- **CRI:** 90+HE
- **Lumen Maintenance:** L70 = >50,000 Hrs.
- **CCT**: Available LED color temperatures: 2700K, 3000K, 3500K, 4000K, 5000K
- **DRIVER:** LED versions feature integral Class 2 power supply standard
- **DIMMING:** 0-10V controls standard to 10% on LED light engines
- **CONTROLS:** Contact factory for control options (e.g., Lutron Athena, Current NX, nLight, Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)
- **EMERGENCY:** Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- **DIFFUSER:** Opal acrylic is standard; matte acrylic and hand painted lenses optional. Any upward facing LEDs will be covered with a protective lens.

- **CONSTRUCTION:** Formed metal construction provides durable protection for internal components and is recyclable
- **MODIFICATIONS:** Consult factory for all modification requests
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

## DIMENSIONS




| W | H | OAH |
|---|---|---|
| 29 in<br>73.7 cm | 9.5 in<br>24.1 cm | 45 in<br>114.3 cm |

**Mounting Weight**
Approximate: 50 lb (23 kg)

## CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/AIP8533. Not all options are available in all configurations; consult factory for details.

**Required Field ***

| Catalog | Light Source* | Primary Finish* | Voltage* | Lamp Options* | CRI* | Diffuser* | Mounting* | Emergency | Bowl Options | Options | Other Than Standard Options |
|---|---|---|---|---|---|---|---|---|---|---|---|
| AIP8533 | | | | | | | | | | | |
| | | | | | | | | | Finish: | Finish: | |
| | A | | B | C | D | E | F | G | H | I | J |

## A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application.

- ☐ **L86W |** White 86W LED Light Engine | Delivered Lumens: 8,475
- ☐ **L172W |** White 172W LED Light Engine | Delivered Lumens: 16,950
- ☐ **Cust_Out |**

**Lumen Calculator:** Enter Lumens or Watts if different than displayed

| | |
|---|---|
| | LU Min 8514 - Max 17028 |
| | W Min 86.0 - Max 172.0 |

See last page for finish options

*For requests outside Min-Max range, please contact factory.

## B - VOLTAGE *

- ☐ 120-277V | Universal Voltage

## C - LAMP OPTIONS *

- ☐ 2700K | 2700K CCT
- ☐ 3000K | 3000K CCT
- ☐ 3500K | 3500K CCT
- ☐ 4000K | 4000K CCT
- ☐ 5000K | 5000K CCT

## D - CRI *

- ☐ DF_90+HE | 90+ High Efficacy

## E - DIFFUSER *

- ☐ DF_OA | Opal Acrylic Diffuser Lens (default)
- ☐ HP01 | Silver Hand Painted Acrylic Diffuser
- ☐ HP02 | Beige Hand Painted Acrylic Diffuser
- ☐ HP03 | Amber Hand Painted Acrylic Diffuser
- ☐ MA01 | Matte Acrylic Diffuser Lens


OA

HP01

HP02

HP03

MA01

## F - MOUNTING *

Mounts to standard 4" octagonal junction box. Canopy features a 45 degree swivel.

- ☐ DF_STM | Stem Mount (default)

## G - EMERGENCY

10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.

- ☐ EMR | Emergency Battery Remote

## H - BOWL OPTIONS

- ☐ FIN | Finial (See last page for finish options)

## I - OPTIONS

- ☐ KA01 | Angled Aircraft Cable Kit (to Transition Plate/Canopy) (See last page for finish options)
- ☐ KR01 | Angled Stem Multi Kit (to Transition Plate) (See last page for finish options)
- ☐ KS01 | Straight Stem Multi Kit (to Transition Plate) (See last page for finish options)
- ☐ F | Fusing

KA01

KR01


KS01

## J - OTHER THAN STANDARD OPTIONS

Specify overall height required from ceiling to the bottom of the fixture.

OAH | Pendant suspension length other than standard Length:

## Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

### Paint Colors

**PT01**
RAL9003 Signal White (Gloss)

**PT51**
Matte White (Textured)

**PT02**
White (Textured)

**PT04**
RAL9001 Cream (Textured)

**PT67**
RAL7044 Silk Grey (Textured)

**PT53**
RAL7035 Light Grey (Textured)

**PT54**
RAL7037 Dusty Grey (Textured)

**PT55**
RAL7012 Basalt Grey (Textured)

**PT56**
RAL7016 Anthracite Grey (Textured)

**PT11**
Black (Textured)

**PT57**
RAL1015 Light Ivory (Textured)

**PT58**
RAL8004 Copper Brown (Textured)

**PT59**
RAL6021 Pale Green (Textured)

**PT60**
RAL1019 Grey Beige (Textured)

**PT61**
RAL7006 Beige Grey (Textured)

**PT62**
RAL1003 Signal Yellow (Textured)

**PT63**
RAL3001 Signal Red (Textured)

**PT64**
RAL6001 Emerald Green (Textured)

**PT65**
RAL5005 Signal Blue (Textured)

**PT66**
RAL5003 Sapphire Blue (Textured)

### Metallic Paint Colors

**PT22**
Platinum (Metallic Gloss)

**PT48**
Brass (Metallic Textured)

**PT28**
Dark Stainless (Metallic Gloss)

**PT49**
Bronze (Metallic Textured)

**PT32**
Dark Bronze (Metallic Gloss)

**PT46**
Aluminum (Metallic Textured)

### Brushed Aluminum

**BAL**
Brushed Aluminum

### Brushed Brass

**BBR**
Brushed Solid Brass

### Polished-Tinted Brass

**ATBR**
Antique Tinted Brass

**DTBR**
Dark Tinted Brass

**PBR**
Polished Brass

### Plated Steel

**ANST**
Antique Brass Plated Steel

**BBST**
Brushed Brass Plated Steel

**CPST**
Chrome Plated Steel

**PBST**
Polished Brass Plated Steel

**SNST**
Satin Nickel Steel

### Polished Plated Brass

**CPBR**
Chrome Plated Polished Brass

**SNBR**
Satin Nickel Plated Brass

## Specialty Finishes

More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies.Call factory for details.