Lightruss Gen 2 - New Construction



LRU12457 34.00 in | Add Ons

JOB NAME: TYPE: NOTES:

DESCRIPTION


Lightruss LED Gen 2 eliminates the need for multiple power drops and electrical conduit.

The dual-rail truss system allows for multiple circuitry, switching, and emergency circuits. The stealth design of Lightruss nests the high-performance luminaires atop the railway system – providing full cut-off and eliminating direct glare all while delivering an impressive 127 lumens per watt. With our innovative indirect lighting system, you can achieve the light levels needed for your projects with less luminaires.

Bonus! Lightruss delivers the lumens and performance needed to meet the NCAA Best Lighting Practices for broadcasting swim/water polo matches.

For a complimentary lighting layout, contact our applications team at SPIteam@spilighting.com.

DIMENSIONS



| | ı | 1 | 1 |
|---------|---------|---------|---|
| W | H | L | |
| 18 in | 4 in | 34 in | |
| 45.7 cm | 10.2 cm | 86.4 cm | ı |

Mounting Weight Consult Factory.

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/LRU12457. Not all options are available in all configurations; consult factory for details.

Required Field *

| Catalog | Light Source* | Primary Finish* | Voltage | Lamp Options | CRI | Controls | Options |
|----------|---------------|-----------------|---------|--------------|-----|----------|---------|
| LRU12457 | | | | | | | |
| | | | | | | | |
| | | Λ | R | C | D | F | F |

A - LIGHT SOURCE *

L524W | 324W Ind / 194W Dir Symmetrical



See last page for finish options

| B - VOLTAGE |
|--|
| ☐ 120-277V Universal Voltage |
| C - LAMP OPTIONS |
| ☐ 2700K 2700K CCT ☐ 3000K 3000K CCT ☐ 3500K 3500K CCT ☐ 4000K 4000K CCT ☐ 5000K 5000K CCT |
| D - CRI |
| □ 90□ 80 (default) |
| E - CONTROLS |
| □ DIM10 0-10V Control, 10% Dimming □ NONE No Controls (default) □ AWNR Lutron Athena Wireless Node, 1% Dimming □ NLTA Acuity nLight Air, 1% Dimming |
| F - OPTIONS |



☐ NAT | Natatorium Construction

Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

| PT01 | PT51 | PT02 | PT04 RAL9001 Cream (Textured) | PT67 |
|---|---------------------------------------|---|---|---|
| RAL9003 Signal White (Gloss) | Matte White (Textured) | White (Textured) | | RAL7044 Silk Grey (Textured) |
| PT53 RAL7035 Light Grey (Textured) | PT54 RAL7037 Dusty Grey (Textured) | PT55 RAL7012 Basalt Grey (Textured) | PT56 RAL7016 Anthracite Grey (Textured) | PT11 Black (Textured) |
| PT57 | PT58 RAL8004 Copper Brown (Textured) | PT59 | PT60 | PT61 |
| RAL1015 Light Ivory (Textured) | | RAL6021 Pale Green (Textured) | RAL1019 Grey Beige (Textured) | RAL7006 Beige Grey (Textured) |
| PT62 RAL1003 Signal Yellow (Textured) | PT63 RAL3001 Signal Red (Textured) | PT64 RAL6001 Emerald Green (Textured) | PT65 RAL5005 Signal Blue (Textured) | PT66 RAL5003 Sapphire Blue (Textured) |

Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.