

Pavo 2" - Wall

SIW12169 2.00 in

SPILIGHTING

PROJECT DETAILS

JOB NAME:

TYPE:


NOTES:

DESCRIPTION

This sleek 2" cylindrical form is a pure expression of light and proof that great design is rooted in simplicity. Pavo 2" Wall is fully illuminated with no housing or metal accents to interrupt its minimalist form. It looks uniform from every angle. Its round diffuser emits a soft gradual display of light on the wall behind the fixture. This low-profile sconce is ADA-compliant and a great choice for hallways, elevator bays, vanities, or anywhere you want to add a simple yet sophisticated line of light. Available in 1' to 6' sizes.

FEATURES & BENEFITS

- The design element you've been missing
- Linearly-lit wall sconce provides even illumination along the entire length of the lens
- Meticulously designed ends have no visible shadowing
- Minimal bracketry and hardware for an exceptionally clean look
- An expression of light in its most basic form
- Provides functional light, up to 750 lumens per foot, with comfortable luminance levels
- Pairs well with the entire Pavo family of pendants
- Mount vertically or horizontally on walls or ceilings
- Compliant with Americans with Disabilities Act (ADA) requirements
- Handcrafted in USA




SPECIFICATIONS

- **LIGHT SOURCE:** White LED light engine
- **CRI:** 80+ or 90+
- **LUMEN MAINTENANCE:** L70 = >50,000 Hrs.
- **EFFICACY:** 107 lm/W delivered
- **CCT:** 2700K, 3000K, 3500K, 4000K, 5000K
- **VOLTAGE:** 120-277V standard
- **DRIVER:** Remote or integral Class 2 power supply. Max distance to the driver is: #18 AWG = 50', #16 AWG = 75', #14 AWG = 100'. For extended distances, contact factory.
- **DIMMING:** 1% minimum dim level standard
- **CONTROLS:** 0-10V standard. Lutron Athena, Current NX, and

nLight AIR optional. Contact factory for other controls (e.g., Enlighted, Encelium, Wattstopper, WaveLinx, or Casambi)

- **EMERGENCY:** Remote battery option is provided with 10W Constant Power Battery back-up, providing 90 Minutes of Emergency operation. Contact factory for other Emergency options.
- **INTEGRATED SURGE PROTECTION:** LED components are protected against minor surge events
- **DIFFUSER:** White matte acrylic
- **CONSTRUCTION:** Aluminum and stainless steel
- **FINISH:** Solid flat end plates and mounting components finished to match. To specify separately, contact factory. Choose from 26 standard thermoset polyester powder coat paint colors or various metal finishes. RAL®, Pantone®, or custom finishes available upon request.
- **MODIFICATIONS:** Consult factory for all modification requests; including different sizes
- **APPROVALS:** ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications

DIMENSIONS



1FT	W 2 in 5.1 cm	H 12 in 30.5 cm	D 2.5 in 6.4 cm	MC 6 in 15.2 cm
-----	----------------------------	------------------------------	------------------------------	------------------------------

Mounting Weight: Approximate: 5 lb (3 kg)

2FT	W 2 in 5.1 cm	H 24 in 61 cm	D 2.5 in 6.4 cm	MC 12 in 30.5 cm
-----	----------------------------	----------------------------	------------------------------	-------------------------------

Mounting Weight: Approximate: 5 lb (3 kg)

3FT	W 2 in 5.1 cm	H 36 in 91.4 cm	D 2.5 in 6.4 cm	MC 18 in 45.7 cm
-----	----------------------------	------------------------------	------------------------------	-------------------------------

Mounting Weight: Approximate: 5 lb (3 kg)

4FT	W 2 in 5.1 cm	H 48 in 121.9 cm	D 2.5 in 6.4 cm	MC 24 in 61 cm
-----	----------------------------	-------------------------------	------------------------------	-----------------------------

Mounting Weight: Approximate: 5 lb (3 kg)

5FT	W 2 in 5.1 cm	H 60 in 152.4 cm	D 2.5 in 6.4 cm	MC 30 in 76.2 cm
-----	----------------------------	-------------------------------	------------------------------	-------------------------------

Mounting Weight: Consult Factory.


6FT	W 2 in 5.1 cm	H 72 in 182.9 cm	D 2.5 in 6.4 cm	MC 36 in 91.4 cm
-----	----------------------------	-------------------------------	------------------------------	-------------------------------

Mounting Weight: Approximate: 5 lb (3 kg)

CONFIGURATOR

To configure your spec sheet online, go to www.spilighting.com/SIW12169. Not all options are available in all configurations; consult factory for details.

Required Field *



A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application. Alternative wattages available upon request.

1 FOOT NOMINAL FIXTURE

1FT-L5W | White 5W LED Light Engine | Delivered Lumens: 537

1FT-L7W | White 7W LED Light Engine | Delivered Lumens: 752

Cust_Out_1FT |

Lumen Calculator: Enter Lumens or Watts if different than displayed

LU Min 535 - Max 749

W Min 5.0 - Max 7.0

2 FOOT NOMINAL FIXTURE

2FT-L7W | White 7W LED Light Engine | Delivered Lumens: 752

2FT-L14W | White 14W LED Light Engine | Delivered Lumens: 1,504

Cust_Out_2FT |

Lumen Calculator: Enter Lumens or Watts if different than displayed

LU Min 749 - Max 1498

W Min 7.0 - Max 14.0

3 FOOT NOMINAL FIXTURE

3FT-L10W | White 10W LED Light Engine | Delivered Lumens: 1,074

3FT-L20W | White 20W LED Light Engine | Delivered Lumens: 2,148

Cust_Out_3FT |

Lumen Calculator: Enter Lumens or Watts if different than displayed

LU Min 1070 - Max 2140

W Min 10.0 - Max 20.0

4 FOOT NOMINAL FIXTURE

4FT-L14W | White 14W LED Light Engine | Delivered Lumens: 1,504

4FT-L28W | White 28W LED Light Engine | Delivered Lumens: 3,007

Cust_Out_4FT |

Lumen Calculator: Enter Lumens or Watts if different than displayed

LU Min 1498 - Max 2996

W Min 14.0 - Max 28.0

5 FOOT NOMINAL FIXTURE

5FT-L18W | White 18W LED Light Engine | Delivered Lumens: 1,933

5FT-L36W | White 36W LED Light Engine | Delivered Lumens: 3,866

Cust_Out_5FT |

Lumen Calculator: Enter Lumens or Watts if different than displayed

LU Min 1926 - Max 3852

W Min 18.0 - Max 36.0

6 FOOT NOMINAL FIXTURE

6FT-L21W | White 21W LED Light Engine | Delivered Lumens: 2,255

6FT-L42W | White 42W LED Light Engine | Delivered Lumens: 4,511

6 FOOT NOMINAL FIXTURE

6FT-L21W | White 21W LED Light Engine | Delivered Lumens: 2,255

6FT-L42W | White 42W LED Light Engine | Delivered Lumens: 4,511

Cust_Out_6FT |

Lumen Calculator: Enter Lumens or Watts if different than displayed

LU Min 2247 - Max 4494

W Min 21.0 - Max 42.0

[See last page for finish options](#)

*For requests outside Min-Max range, please contact factory.

B - VOLTAGE *

120-277V | Universal Voltage

C - LAMP OPTIONS *

Apply multiplier from chart for delivered lumens at other CCT's and CRI's.

2700K | 2700K CCT

3000K | 3000K CCT

3500K | 3500K CCT

4000K | 4000K CCT

5000K | 5000K CCT

	80 CRI	90 CRI
2700K	0.91	0.77
3000K	0.94	0.80
3500K	0.97	0.82
4000K	1.00	0.85
5000K	1.00	0.85

D - CRI *

DF_80 | (default)

90

E - CONTROLS *

Extended lead times may apply for controls other than 0-10V. Contact factory for additional control options such as Enlighted, Encelium, Wattstopper, WaveLinx, Casambi, or others.

- DF_DIM1 | 0-10V Control, 1% Dimming (default)
- AWRN ¹ | Lutron Athena Wireless Node, 1% Dimming
- NX ¹ | Current NX Wireless, 1% Dimming
- NLTA ¹ | Acuity nLight Air, 1% Dimming

¹ Not available with REC mounting option.

F - DIFFUSER *

- DF_MA01 | Matte Acrylic Diffuser Lens (default)
- OA | White Gloss Acrylic Diffuser
- HP01- 1' | Silver Hand Painted Acrylic Diffuser
- HP02- 1' | Beige Hand Painted Acrylic Diffuser
- HP03- 1' | Amber Hand Painted Acrylic Diffuser
- HP01- 2' | Silver Hand Painted Acrylic Diffuser
- HP02- 2' | Beige Hand Painted Acrylic Diffuser
- HP03- 2' | Amber Hand Painted Acrylic Diffuser
- HP01- 3' | Silver Hand Painted Acrylic Diffuser
- HP02- 3' | Beige Hand Painted Acrylic Diffuser
- HP03- 3' | Amber Hand Painted Acrylic Diffuser
- HP01- 4' | Silver Hand Painted Acrylic Diffuser
- HP02- 4' | Beige Hand Painted Acrylic Diffuser
- HP03- 4' | Amber Hand Painted Acrylic Diffuser
- HP01- 6' | Silver Hand Painted Acrylic Diffuser
- HP02- 6' | Beige Hand Painted Acrylic Diffuser
- HP03- 6' | Amber Hand Painted Acrylic Diffuser



G - MOUNTING *


MCS mounting supplied with 8' lead length and 2.25" round goof plates. REC mounting requires a cut-out for the recessed box that measures 1.75" wide by a height calculated as MC plus 3" and a minimum wall cavity depth of 3.5". Consider wall framing accordingly, as the application requires.

- MCS | Invisible Stems, Remote Power Supply
- REC | Recessed, Integral Power Supply
- JBC01 ² | 5" Round J-box Cover, Remote Power Supply
- JBC02 ² | 4.3" Square J-box Cover, Remote Power Supply


² Only available in 1', 2', or 3' sizes




MCS



REC



JBC01



JBC02

H - EMERGENCY

10W, Constant Power Battery Back-up, with 90 minutes of emergency operation. EMR includes damp location enclosure for Battery back-up.

- EMR | Emergency Battery Remote

Standard Finishes

The colors shown are representative. Their actual appearance may vary due to differences in display settings. You can request color chips by emailing contact@spilighting.com. Please note, finishes may not be available in all configurations.

Paint Colors

PT01 RAL9003 Signal White (Gloss)	PT51 Matte White (Textured)	PT02 White (Textured)	PT04 RAL9001 Cream (Textured)	PT67 RAL7044 Silk Grey (Textured)
PT53 RAL7035 Light Grey (Textured)	PT54 RAL7037 Dusty Grey (Textured)	PT55 RAL7012 Basalt Grey (Textured)	PT56 RAL7016 Anthracite Grey (Textured)	PT11 Black (Textured)
PT57 RAL1015 Light Ivory (Textured)	PT58 RAL8004 Copper Brown (Textured)	PT59 RAL6021 Pale Green (Textured)	PT60 RAL1019 Grey Beige (Textured)	PT61 RAL7006 Beige Grey (Textured)
PT62 RAL1003 Signal Yellow (Textured)	PT63 RAL3001 Signal Red (Textured)	PT64 RAL6001 Emerald Green (Textured)	PT65 RAL5005 Signal Blue (Textured)	PT66 RAL5003 Sapphire Blue (Textured)

Metallic Paint Colors

PT22 Platinum (Metallic Gloss)	PT48 Brass (Metallic Textured)	PT28 Dark Stainless (Metallic Gloss)	PT49 Bronze (Metallic Textured)	PT32 Dark Bronze (Metallic Gloss)
PT46 Aluminum (Metallic Textured)				

Brushed Aluminum

BAL Brushed Aluminum

Specialty Finishes



More RAL®, Pantone®, and custom finishes are available upon request. Setup fee and additional lead time applies. Call factory for details.